

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction SE $\frac{1}{4}$ NE $\frac{1}{4}$ NE $\frac{1}{4}$	Section Number 28	Township Number T 27 S	Range Number R 3 E E/W		
Distance and direction from nearest town or city street address of well if located within city? 2 miles E. of Andover - Rose Hill Rd., on 54 Hyway, $\frac{1}{4}$ S. of that Rd., Wichita, Ks.							
2 WATER WELL OWNER:		Jim Hying 16290 Tower Lane Wichita, Ks.		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 65 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 25 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr 4/13/81 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 11 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No					
5 TYPE OF BLANK CASING USED:		5 Wrought iron 1 Steel 2 PVC	8 Concrete tile 6 Asbestos-Cement 7 Fiberglass	CASING JOINTS: Glued X Clamped Welded Threaded			
Blank casing diameter 5 in. to 20 ft., Dia in. to ft., Dia in. to ft.							
Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No. , 203							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement Same 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SDR-26 12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 06 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS: From 20 ft. to 65 ft., From ft. to ft.							
From ft. to ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From 14 ft. to 65 ft., From ft. to ft.							
From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL:		1 Neat cement Grout Intervals: From 40 ft. to 14 ft., From ft. to ft., From ft. to ft.	2 Cement grout From ft. to ft., From ft. to ft., From ft. to ft.	3 Bentonite From ft. to ft., From ft. to ft.	4 Other		
What is the nearest source of possible contamination:							
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)							
Direction from well? East		How many feet? 80					
FROM	TO	LITHOLOGIC LOG		FROM	TO	LITHOLOGIC LOG	
0	3	Topsoil					
3	8	Brown Clay					
8	13	Light Tan Clay					
13	25	Light Tan Shale					
25	65	Blue Shale					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/13/81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 6-15-81 under the business name of Harp Well & Pump Serv., Inc. by (signature) <i>M. Arnold</i>							
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.							