


1 LOCATION OF WATER WELL: Butler	FRACTION NE 1/4 NE 1/4 NE 1/4	Section Number 28	Township Number T 27 S	Range Number R 3E EW
Distance and direction from nearest town or city street address of well if located within city? 2 mi. E. of Andover Rd., 1/8 S. of Hwy 54, Westside Andover, Kansas				
2 WATER WELL OWNER: KLEEN KUT	RR#, ST. ADDRESS, BOX #: 330 S. 160th E	Board of Agriculture, Division of Water Resource		
CITY, STATE, ZIP CODE: Andover, Kansas	67230	Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL Depth(s) groundwater Encountered 80	ft. ELEVATION: ft. 2 ft. 3 ft. 20 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 04/20/1994		
	Pump test data: Est. Yield 80 gpm: Bore Hole Diameter 12 in.	Well water was ft. after hours pumping gpm Well water was ft. after hours pumping gpm to 80 ft. and in. to ft.		
	WELL WATER TO BE USED AS: 1 Domestic 2 Irrigation	5 Public water supply 6 Oil field water supply 7 Lawn and garden only	8 Air conditioning 9 Dewatering 10 Monitoring well	11 Injection well 12 Other (Specify below)
	Was a chemical/bacteriological sample submitted to Department? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> ; If yes, mo/day/yr sample was submitted			
5 TYPE OF CASING USED: 1 Steel 2 PVC	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (Specify below)	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped Welded Threaded	
Blank casing Diameter 5 in. to 25	ft., Dia weight 2.35	in. to ft., Dia lbs. / ft. 7 PVC	in. to ft. Wall thickness or gauge No. .214 10 Asbestos-cement	
Casing height above land surface 12 in.				
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass				
1 Steel 2 Brass	3 Stainless Steel 4 Galvanized steel	5 Fiberglass 6 Concrete tile	8 RMP (SR) 9 ABS	11 other (specify) 12 None used (open hole)
SCREEN OR PERFORATION OPENING ARE: 1 Continous slot 2 Louvered shutter				
1 Continous slot 2 Louvered shutter	3 Mill slot 4 Key punched	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)
SCREEN-PERFORATION INTERVALS: from 25 ft. to 80 ft., From ft. to ft.				
GRAVEL PACK INTERVALS: from 24 ft. to 80 ft., From ft. to ft.				
6 GROUT MATERIAL: 1 Neat cement	2 Cement grout	3 Bentonite	4 Other	
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.				
What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines				
1 Septic tank 2 Sewer lines 3 Watertight sewer lines	4 Lateral lines 5 Cess pool 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandon water well 15 Oil well/Gas well 16 Other (specify below) None Apparent
Direction from well?				
FROM		TO	LITHOLOGIC LOG	
0	3	topsoil	FROM	TO
3	6	clay		
6	43	brown shale		
43	80	grey shale		
PLUGGING INTERVALS				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 04/20/1994 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 04/23/94 . Under the business name of Harp Well & Pump Service, Inc. by (signature) Jane Frederick				