

1 LOCATION OF WATER WELL:		Fraction SE $\frac{1}{4}$ SW $\frac{1}{4}$ SW $\frac{1}{4}$	Section Number 29	Township Number T 27 S	Range Number R 3 E E/W
Distance and direction from nearest town or city street address of well if located within city?					
1502 Phyllis Andover, Kansas					
2 WATER WELL OWNER:		Tom Schiller			
RR#, St. Address, Box #		1502 Phyllis			
City, State, ZIP Code		Andover, Ks.			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL... 80 ft. ELEVATION: ft. Depth(s) Groundwater Encountered 1. 15 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 1.5 ft. below land surface measured on mo/day/yr 10-5-84 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 1.1 in. to 80 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes. No. XX. If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes. XX. No			
5 TYPE OF BLANK CASING USED:		1 Steel 3 RMP (SR) 2 PVC 4 ABS X	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (specify below) Cer-Mac styrene SDR-26	CASING JOINTS: Glued. XX. Clamped. Welded. Threaded.
Blank casing diameter 5 in. to 12 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface. X 5 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 203					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 2 Brass 4 Galvanized steel		5 Fiberglass 6 Concrete tile = 9 ABS	7 PVC 8 RMP (SR) = 9 ABS	10 Asbestos-cement 11 Other (specify) 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched		5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)	
SCREEN-PERFORATED INTERVALS: From. 60 ft. to 80 ft., From. ft. to ft. From. ft. to ft.					
GRAVEL PACK INTERVALS: From. 14 ft. to 80 ft., From. ft. to ft. From. ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From. 4 ft. to 14 ft., From. ft. to ft., From. ft. to ft., From. ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool X 3 Watertight sewer lines 6 Seepage pit		7 Pit privy 8 Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)	
Direction from well? == West How many feet? 85					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-5-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236. This Water Well Record was completed on (mo/day/yr) 4-15-85 under the business name of Harp Well & Pump Service, Inc. by (signature) Mary Arnold					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					