


1 LOCATION OF WATER WELL:		Fraction NW $\frac{1}{4}$ NW $\frac{1}{4}$ NW $\frac{1}{4}$	Section Number 29	Township Number T 27 S	Range Number R 3 (E/W)			
County: Butler		Distance and direction from nearest town or city street address of well if located within city?						
2 WATER WELL OWNER: National Bank of Andover		HWST Job No.: 70-74-40/4029.01						
RR#, St. Address, Box #: 225 W. Central		Board of Agriculture, Division of Water Resources						
City, State, ZIP Code: Andover, KS		Application Number:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 17.0 ft. ELEVATION: n/a						
		Depth(s) Groundwater Encountered 1. 10.5 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 9.65 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 6.5 in. to 17.0 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well No. 3 Was a chemical/bacteriological sample submitted to Department? Yes. No. x. If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No x						
5 TYPE OF BLANK CASING USED:		5 Wrought iron 1 Steel 2 PVC	8 Concrete tile 6 Asbestos-Cement 7 Fiberglass	CASING JOINTS: Glued Clamped Welded Threaded x				
Blank casing diameter 2.0 in. to 17.0 ft., Dia		in. to ft., Dia in. to ft.						
Casing height above land surface flush in., weight		lbs./ft. Wall thickness or gauge No. Sch. 40						
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 5 Fiberglass 6 Concrete tile	10 Asbestos-cement 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)				
1 Continuous slot 2 Louvered shutter		3 Mill slot 4 Key punched						
SCREEN-PERFORATED INTERVALS: From 7 ft. to 17 ft.		From ft. to ft.						
From ft. to ft.		From ft. to ft.						
GRAVEL PACK INTERVALS: From 5 ft. to 17 ft.		From ft. to ft.						
From ft. to ft.		From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement		2 Cement grout 3 Bentonite	4 Other Volclay Grout					
Grout Intervals: From 0 ft. to 3 ft.		From ft. to ft.	From ft. to ft.					
What is the nearest source of possible contamination:		7 Pit privy 8 Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)				
Direction from well? W		How many feet? 60						
FROM		TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS	
0	4.0		Silty clay - dark brown, 0-10% calcareous, fine sand, moist.					
4.0	6.0		Silty clay - dark brown and olive, 0-5% calcareous fine gravels, wet.					
6.0	17.0		Silty Clay - mottled light yellow, brown and olive, 20-30% limestone cobbles, very wet, saturated at 10.5 feet.					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/24/00 and this record is true to the best of my knowledge and belief, Kansas.

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.