

1 LOCATION OF WATER WELL:		Fraction County: Butler	NE $\frac{1}{4}$ NE $\frac{1}{4}$ NE $\frac{1}{4}$	Section Number 30	Township Number T 27 S	Range Number R 3 EW
Distance and direction from nearest town or city street address of well if located within city? Southwest corner of Hwy 54 & Andover Rd; Andover KS						
2 WATER WELL OWNER:		Town & Country Markets P.O. Box 17087 Wichita KS 67217		Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 150 ft. ELEVATION: NA				
		Depth(s) Groundwater Encountered 1. 13.20 ft. 2. ft. 3. ft.				
		WELL'S STATIC WATER LEVEL NA ft. below land surface measured on mo/day/yr NA				
		Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to ft., and in. to ft.				
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well				
		Was a chemical/bacteriological sample submitted to Department? Yes No. If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X				
5 TYPE OF BLANK CASING USED:		5 Wrought iron 1 Steel 2 PVC	8 Concrete tile 6 Asbestos-Cement 7 Fiberglass	CASING JOINTS: Glued Clamped Welded Threaded Flush		
Blank casing diameter		2 in. to ft.	Dia in. to ft.	Dia in. to ft.	in. to ft.	
Casing height above land surface		Flush in. weight	70.3	lbs./ft. Wall thickness or gauge No.	154	
TYPE OF SCREEN OR PERFORATION MATERIAL:		5 Fiberglass 2 Brass 4 Galvanized steel	8 RMP (SR) 6 Concrete tile 9 ABS	10 Asbestos-cement 11 Other (specify) 12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 1 Continuous slot 2 Louvered shutter	8 Saw cut 6 Wire wrapped 7 Torch cut	11 None (open hole) 9 Drilled holes 10 Other (specify)		
SCREEN-PERFORATED INTERVALS:		From 4.55 ft. to 14.55 ft.	From ft. to ft.	ft. to ft.	ft. to ft.	
GRAVEL PACK INTERVALS:		From 3.55 ft. to 14.55 ft.	From ft. to ft.	ft. to ft.	ft. to ft.	
6 GROUT MATERIAL:		1 Neat cement Grout Intervals: From 3.55 ft. to 10 ft.	2 Cement grout From ft. to ft.	3 Bentonite 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	4 Other 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)	
What is the nearest source of possible contamination:		4 Lateral lines 2 Sewer lines 3 Watertight sewer lines	7 Pit privy 8 Sewage lagoon 9 Feedyard	How many feet? 60		
Direction from well?		East				
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS
0.0	3.0	Clay, moist, plastic				
3.0	13.5	Shale, slightly weathered soft, limestone nodules, moist				
13.5	15.0	Shale, slightly weathered soft, moist				
Flush mount waiver granted on 9-18-92 for KDHE project # 02008061 by Don Taylor						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-8-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 10-23-92 under the business name of Geotechnical Services, Inc. by (signature) Allison Truett						