

1 LOCATION OF WATER WELL:		Fraction County: Butler	NE $\frac{1}{4}$ NE $\frac{1}{4}$ NE $\frac{1}{4}$	Section Number 30	Township Number T 27 S	Range Number R 3 E
Distance and direction from nearest town or city street address of well if located within city? South west corner of Hwy 54 & Andover Rd; Andover KS						
2 WATER WELL OWNER:		Town & Country Markets P.O. Box 17087 Wichita, KS 67217		Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 15.0 ft. ELEVATION: NA Depth(s) Groundwater Encountered 1. NA ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL NA ft. below land surface measured on mo/day/yr NA Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X				
5 TYPE OF BLANK CASING USED:		1 Steel 3 RMP (SR) 2 PVC 4 ABS	5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass	CASING JOINTS: Glued Clamped Welded Threaded Flush		
Blank casing diameter		Z in. to ft. Dia in. to ft. Dia in. to ft.	lbs./ft. Wall thickness or gauge No. 154			
Casing height above land surface		Flush in. weight 70.3	7 PVC			
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel 3 Stainless steel 2 Brass 4 Galvanized steel		5 Fiberglass 8 RMP (SR) 6 Concrete tile 9 ABS	10 Asbestos-cement 11 Other (specify) 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)	11 None (open hole)			
1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched		4.55				
SCREEN-PERFORATED INTERVALS: From		14.55 ft. to ft. From ft. to ft.				
From		ft. to ft. From ft. to ft.				
GRAVEL PACK INTERVALS: From		3.55 ft. to 14.55 ft. From ft. to ft.				
From		ft. to ft. From ft. to ft.				
6 GROUT MATERIAL: 1 Neat cement Grout Intervals: From 3.55 ft. to 1.0 ft., From		2 Cement grout 3 Bentonite	4 Other 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage How many feet? ~30			
What is the nearest source of possible contamination:		7 Pit privy 8 Sewage lagoon 9 Feedyard	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)			
1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit						
Direction from well? SW						
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0.0	2.0	Clay, very plastic, moist				
2.0	8.5	Shale, weathered, slightly moist				
8.5	13.5	Shale, highly weathered, soft, moist				
13.5	15.0	Shale, highly weathered, soft, moist				

Flush Mount waiver granted on 9-18-92
for KDHE Project # 02008061 by Don Taylor

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-9-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. S31 This Water Well Record was completed on (mo/day/yr) 10-23-92 under the business name of Geotechnical Services, Inc. by (signature) Allison Irvin