


1	LOCATION OF WATER WELL: Butler	FRACTION NW 1/4 SE 1/4 NE 1/4	Section Number 30	Township Number T 27 S	Range Number R 3E EW	
Distance and direction from nearest town or city street address of well if located within city?						
1/4 S. of Hwy. 54, 1/4 W. of Andover Rd., E. side of Allen St. Andover, Ks.						
2	WATER WELL OWNER: REZNICK, Joseph	RR#, ST. ADDRESS, BOX #: 1217 S. Paige #203	Board of Agriculture, Division of Water Resource			
CITY, STATE, ZIP CODE: Wichita, Kansas		67207	Application Number:			
3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4	DEPTH OF COMPLETED WELL 75 ft.	ELEVATION: ft. below land surface measured on mo/day/yr 07/01/1992		
Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 75 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well						
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No						
5	TYPE OF CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS					CASING JOINTS: Glued X Clamped Welded Threaded
Blank casing Diameter 5 in. to 35 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 2.29 lbs./ft.						Wall thickness or gauge No. .214 10 Asbestos-cement
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 2 Brass 4 Galvanized steel						5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS
SCREEN OR PERFORATION OPENING ARE: 1 Continous slot 3 Mill slot 2 Louvered shutter 4 Key punched						5 Gauzed wrapped 6 Wire wrapped 7 Torch cut
SCREEN-PERFORATION INTERVALS: from 35 ft. to 75 ft., From ft. to ft. from ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: from 24 ft. to 75 ft., From ft. to ft.						8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)
6	GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.						10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit						14 Abandon water well 15 Oil well/Gas well 16 Other (specify below)
						None Apparent
Direction form well?						How many feet?
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS
0	3	topsoil				
3	16	clay				
16	53	brown shale				
53	75	grey shale				
7	CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 07/01/1992 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 11/05/92 . Under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Jane Frederick</i>					