

1 LOCATION OF WATER WELL:		Fraction NE $\frac{1}{4}$ NE $\frac{1}{4}$ NE $\frac{1}{4}$	Section Number 31	Township Number T 27 S	Range Number R 3 E EW		
Distance and direction from nearest town or city street address of well if located within city? 16000 Calvacade Off of Rose Hill Road, 2 blks. So. of Harry, Rose Hill, Ks.							
2 WATER WELL OWNER: Dennis Hall		Board of Agriculture, Division of Water Resources Application Number:					
RR#, St. Address, Box #: 16000 Calvacade							
City, State, ZIP Code : Wichita, Kansas							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 50 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 18 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 11-14-83 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 11 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No					
5 TYPE OF BLANK CASING USED:		1 Steel 3 RMP (SR)	5 Wrought iron 6 Asbestos-Cement	8 Concrete tile 9 Other (specify below)	CASING JOINTS: Glued X Clamped Welded		
2 PVC 4 ABS		7 Fiberglass	. Cer-Mac. styrene SDR-26 Threaded				
Blank casing diameter 5 in. to 15 ft., Dia.		in. to ft., Dia. in. to ft.					
Casing height above land surface 12 in., weight 1.59 lbs./ft.		Wall thickness or gauge No. 203					
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel 3 Stainless steel		5 Fiberglass	7 PVC 8 RMP (SR)	10 Asbestos-cement 11 Other (specify)			
2 Brass 4 Galvanized steel		6 Concrete tile	9 ABS	12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot 3 Mill slot		5 Gauzed wrapped	8 Saw cut	11 None (open hole)			
2 Louvered shutter 4 Key punched		6 Wire wrapped	9 Drilled holes	10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 15 ft. to 50 ft.		7 Torch cut					
GRAVEL PACK INTERVALS: From 14 ft. to 50 ft.		From ft. to ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.		
6 GROUT MATERIAL: 1 Neat cement		2 Cement grout	3 Bentonite	4 Other			
Grout Intervals: From 4 ft. to 14 ft.		From ft. to ft.	From ft. to ft.	From ft. to ft.			
What is the nearest source of possible contamination:							
1 Septic tank 4 Lateral lines		7 Pit privy	10 Livestock pens	14 Abandoned water well			
2 Sewer lines 5 Cess pool		8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well			
3 Watertight sewer lines 6 Seepage pit		9 Feedyard	12 Fertilizer storage	16 Other (specify below)			
13 Insecticide storage None. Apparent							
Direction from well? How many feet?							
FROM	TO	LITHOLOGIC LOG		FROM	TO	LITHOLOGIC LOG	
0	3	Topsoil					
3	15	D/Clay					
15	17	o7 Fine Sand					
17	50	/9 Grey Shale					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-14-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236. This Water Well Record was completed on (mo/day/yr) 3-5-84							
under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Mary Arnold</i>							
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.							