


WATER WELL RECORD

Form WWC-5

KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction NE 1/4 NE 1/4 NE 1/4	Section Number 31	Township Number T 27 S	Range Number R 3 E EW		
Distance and direction from nearest town or city street address of well if located within city?							
16000 Calvacade Off of Rose Hill Road, 2 blks. So. of Harry, Rose Hill, Ks.							
2 WATER WELL OWNER: Dennis Hall		Board of Agriculture, Division of Water Resources					
RR#, St. Address, Box # : 16000 Calvacade		Application Number:					
City, State, ZIP Code : Wichita, Kansas							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL..... 50 ft. ELEVATION:					
		Depth(s) Groundwater Encountered 1. 18 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 11-14-83.83 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 11 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 <u>Lawn and garden only</u> 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No					
5 TYPE OF BLANK CASING USED:		5 Wrought iron 1 Steel 3 RMP (SR) 2 PVC 4 ABS	6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (specify below) 7 PVC	CASING JOINTS: Glued X Clamped Welded Threaded		
Blank casing diameter 5 in. to 20		ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 12		in., weight 1.59	lbs./ft. Wall thickness or gauge No. 20.3				
TYPE OF SCREEN OR PERFORATION MATERIAL:		5 Fiberglass 2 Brass 4 Galvanized steel	6 Concrete tile	7 PVC 8 RMP (SR) 9 ABS	10 Asbestos-cement 11 Other (specify) 12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:		1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)		
SCREEN-PERFORATED INTERVALS: From 20		ft. to 50	ft., From ft. to ft.				
From ft. to ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From 14		ft. to 50	ft., From ft. to ft.				
From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement		2 Cement grout	3 Bentonite	4 Other			
Grout Intervals: From 4		ft. to 14	ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:							
1 Septic tank 2 Sewer lines 3 Watertight sewer lines		4 Lateral lines 5 Cess pool 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) 17 None. Apparent		
Direction from well?							
FROM	TO	LITHOLOGIC LOG		FROM	TO	LITHOLOGIC LOG	
0	3	Topsoil					
3	18	Clay					
18	27	Fine Sand & Shale Rock					
27	50	Grey Shale					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-14-83 and this record is true to the best of my knowledge and belief. Kansas							
Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 3-5-84 under the business name of Harp Well & Pump Service, Inc.						by (signature) <i>Mary Arnold</i>	
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.							