


Form WWC-5 KSA 82a-1212

KSA 82a-1212

1 LOCATION OF WATER WELL:	Fraction County: BUTLER	NE $\frac{1}{4}$ SW $\frac{1}{4}$ NE $\frac{1}{4}$	Section Number 31	Township Number T 27 S	Range Number R 3
Distance and direction from nearest town or city street address of well if located within city? 1 1/4 S. Andover					
2 WATER WELL OWNER:	L.G. Langston		Board of Agriculture, Division of Water Resources Application Number:		
RR#, St. Address, Box #	401 N. Woodlawn				
City, State, ZIP Code	Wichita, KS 67218				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 36	ft. ELEVATION: 36	
			Depth(s) Groundwater Encountered: 1. 30	ft. 2. 30 ft. 3. 30 ft.	
			WELL'S STATIC WATER LEVEL: 12	ft. below land surface measured on mo/day/yr 6/4/53	
			Pump test data: Well water was ft. after hours pumping gpm		
			Est. Yield: 40 gpm: Well water was ft. after hours pumping gpm		
			Bore Hole Diameter: 10 in. to ft. and in. to ft.		
			WELL WATER TO BE USED AS:	5 Public water supply	8 Air conditioning
			Domestic	3 Feedlot	9 Dewatering
			2 Irrigation	4 Industrial	10 Monitoring well
			Was a chemical/bacteriological sample submitted to Department? Yes ✓ No ✓	If yes, mo/day/yr sample was submitted	
			Water Well Disinfected? Yes ✓ No ✓		
5 TYPE OF BLANK CASING USED:	1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS Glued ✓ Clamped
	PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
	Blank casing diameter: 5 in. to ft.		7 Fiberglass	Threaded	
	Casing height above land surface: 12 in., weight: 160 lbs./ft.		7 PVC	Wall thickness or gauge No.	
	TYPE OF SCREEN OR PERFORATION MATERIAL:		5 Fiberglass	10 Asbestos-cement	
	1 Steel	3 Stainless steel	6 Concrete tile	11 Other (specify)	
	2 Brass	4 Galvanized steel	7 Gauzed wrapped	12 None used (open hole)	
	1 Continuous slot	3 Mill slot	8 Wire wrapped	13 Saw cut	11 None (open hole)
	2 Louvered shutter	4 Key punched	9 Torch cut	9 Drilled holes	
	SCREEN-PERFORATED INTERVALS: From: 16 ft. to 36 ft.		10 Other (specify)		
	From: 16 ft. to 36 ft.		ft. From: 16 ft. to 36 ft.	ft. From: 16 ft. to 36 ft.	ft.
	GRAVEL PACK INTERVALS: From: 20 ft. to 36 ft.		ft. From: 20 ft. to 36 ft.	ft. From: 20 ft. to 36 ft.	ft.
	From: 20 ft. to 36 ft.		ft. From: 20 ft. to 36 ft.	ft. From: 20 ft. to 36 ft.	ft.
6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other	
Grout Intervals:	From: 3 ft. to 20 ft.	From: 3 ft. to 20 ft.	From: 3 ft. to 20 ft.	From: 3 ft. to 20 ft.	ft.
What is the nearest source of possible contamination:					
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well	
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well	
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)	
Direction from well?	Down Slope				
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	EARTH			
4	12	RED Clay			
12	36	Gray Shale Lime			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:	This water well was 1 constructed, 2 reconstructed, or 3 plugged under my jurisdiction and was completed on (mo/day/year) 6/4/53 and this record is true to the best of my knowledge and belief. Kansas				
Water Well Contractor's License No. 493	This Water Well Record was completed on (mo/day/year) 6/4/53 by (signature) Denny Rizner				
under the business name of Resear Well Drilling					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					