

LOCATION OF WATER WELL:				FRACTION	Section Number	Township Number	Range Number
Butler				SW 1/4 NE 1/4 NE 1/4	7	T 27 S	R 3E E/W
Distance and direction from nearest town or city street address of well if located within city?							
At Marc & Grace Streets, 100' W. on S. side of Grace St. Andover, Kansas							
WATER WELL OWNER: BUILDER DEVELOPMENT INC.				Board of Agriculture, Division of Water Resource			
RR#, ST. ADDRESS, BOX #: 1097 S. Glendale (Parklane Office Park)				Application Number:			
CITY, STATE, ZIP CODE: Wichita, Kansas 67218							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:				4 DEPTH OF COMPLETED WELL 90 ft. ELEVATION:			
				Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. 4 ft. <b>WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 09/13/1994</b> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 90 ft. and in. to ft. <b>WELL WATER TO BE USED AS:</b> 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> ; If yes, mo/day/yr sample was submitted				Water Well Disinfected? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>			
5 TYPE OF CASING USED:				CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped			
1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	9 Other (Specify below)	Welded		
2 PVC	4 ABS	6 Asbestos-Cement	7 Fiberglass	<b>SDR-26</b>	Threaded		
Blank casing Diameter 5 in. to 30	ft., Dia	in. to	ft., Dia	in. to	ft.		
Casing height above land surface 12 in.,	weight 2.35 lbs. / ft.	7 PVC	Wall thickness or gauge No. 10 Asbestos-cement	.214			
TYPE OF SCREEN OR PERFORATION MATERIAL:				11 other (specify)			
1 Steel	3 Stainless Steel	5 Fiberglass	8 RMP (SR)	12 None used (open hole)			
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS				
SCREEN OR PERFORATION OPENING ARE:				8 Saw cut 11 None (open hole)			
1 Continous slot	3 Mill slot	5 Gauzed wrapped	9 Drilled holes				
2 Louvered shutter	4 Key punched	6 Wire wrapped	10 Other (specify)				
SCREEN-PERFORATION INTERVALS: from 30 ft. to 90 ft. From ft. to ft.							
GRAVEL PACK INTERVALS: from 24 ft. to 90 ft. From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandon water well			
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well			
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)			
Direction from well? <b>East</b> How many feet? <b>15</b>							
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS	
0	3	topsoil					
3	11	clay					
11	62	brown shale					
62	90	grey shale					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <b>09/13/1994</b> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <b>236</b> This Water Well Record was completed on (mo/day/yr) <b>09/15/94</b> . Under the business name of <b>Harp Well &amp; Pump Service, Inc.</b> by (signature) <b>Jane Frederick</b>							