


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number		
County: Butler 008		NW $\frac{1}{4}$ NW $\frac{1}{4}$ NW $\frac{1}{4}$	29	T 27 S	R 3 EW		
Distance and direction from nearest town or city street address of well if located within city?							
524 S. Andover Rd							
2 WATER WELL OWNER:		Town & Country Markets PO Box 17087 Wichita KS 67217					
RR#, St. Address, Box # :		Board of Agriculture, Division of Water Resources					
City, State, ZIP Code :		Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 17 ft. ELEVATION:					
		Depth(s) Groundwater Encountered 1. 15.34 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 1023 ft. below land surface measured on mo/day/yr 12-21-94 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <input checked="" type="checkbox"/>					
5 TYPE OF BLANK CASING USED:							
1 Steel <input checked="" type="checkbox"/>		3 RMP (SR)		5 Wrought iron			
2 Brass <input checked="" type="checkbox"/>		4 ABS		6 Asbestos-Cement			
Blank casing diameter 2 in. to ft.		Dia. in. to ft.		8 Concrete tile			
Casing height above land surface <u>Flush</u> in. weight 703 lbs./ft. Wall thickness or gauge No. 154							
Casing joints: Glued Clamped Welded Threaded <u>Flush</u>							
6 TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel		3 Stainless steel		5 Fiberglass			
2 Brass		4 Galvanized steel		6 Concrete tile			
7 PVP							
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot		3 Mill slot		5 Gauzed wrapped			
2 Louvered shutter		4 Key punched		6 Wire wrapped			
SCREEN-PERFORATED INTERVALS: From 7 ft. to 17 ft.		From ft. to ft.		8 Saw cut			
GRAVEL PACK INTERVALS: From 5 ft. to 17 ft.		From ft. to ft.		9 Drilled holes			
From ft. to ft.		From ft. to ft.		10 Other (specify)			
11 None (open hole)							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 5 ft. to 1 ft. From ft. to ft. From ft. to ft. From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank		4 Lateral lines		7 Pit privy			
2 Sewer lines		5 Cess pool		8 Sewage lagoon			
3 Watertight sewer lines		6 Seepage pit		9 Feedyard			
10 Livestock pens							
11 Fuel storage							
12 Fertilizer storage							
13 Insecticide storage							
14 Abandoned water well							
15 Oil well/Gas well							
16 Other (specify below)							
Direction from well? <u>North</u>							
How many feet? 170							
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS	
0.0	1.0	Dirt/gravel fill					
1.0	3.0	Clay, Silty					
3.0	3.5	Limestone lenses					
3.5	6.5	Clay, Silty, Slightly Sandy					
6.5	13.5	Clay, Silty					
13.5	17.0	Clay, Silty, Caliche Nodules					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-21-94						and this record is true to the best of my knowledge and belief. Kansas	
Water Well Contractor's License No. 531						This Water Well Record was completed on (mo/day/yr) 1-20-95	