

1 LOCATION OF WATER WELL:		Fraction County: Butler Distance and direction from nearest town or city/street address of well if located within city?	Section Number 22	Township Number T 27 S	Range Number R 4 E	
2 WATER WELL OWNER:		Frank Witwell Augusta Kan RR#, St. Address, Box #: #16 WoodLand 67010				
		Board of Agriculture, Division of Water Resources Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 125 ft. ELEVATION: 193 ft. 2. ft. 3. ft. Depth(s) Groundwater Encountered 193 ft. below land surface measured on mo/day/yr WELL'S STATIC WATER LEVEL 50 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield 50 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7/8 in. to ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No. If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No				
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped <input type="checkbox"/> 1 Steel 3 RMP (SR) 6 Asbestos-Cement Welded <input type="checkbox"/> 2 PVC 4 ABS 7 Fiberglass Threaded <input type="checkbox"/> Blank casing diameter 3 in. to 60 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface 18 in., weight 160 lbs./ft. Wall thickness or gauge No. 1214				
6 SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)				
SCREEN-PERFORATED INTERVALS:		From 60 ft. to 125 ft. From ft. to ft. From ft. to ft. From ft. to ft.				
GRAVEL PACK INTERVALS:		From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft.				
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 23 ft., From ft. to ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)				
Direction from well?		S 85 ft. How many feet?				
FROM		TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0		4	SOIL			
4		8	ROCK			
8		24	CLAY			
27		125	STALLET LIME			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:		This water well was 11 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/1/96 and this record is true to the best of my knowledge and belief. Kansas				
Water Well Contractor's License No. 251		This Water Well Record was completed on (mo/day/year) 9/1/96 by (signature) <i>Charles Winter</i>				
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						