


| | | | | | |
|--|--|--|--|---|------------------------------------|
| 1 | LOCATION OF WATER WELL: Butler | FRACTION SE 1/4 NE 1/4 NW 1/4 | Section Number 20 | Township Number T 27 S | Range Number R 4E E/W |
| Distance and direction from nearest town or city street address of well if located within city? | | | | | |
| Andover Rd. & 90th St. N., 3/8 m. E. & 1/4 m. S. Andover, KS. | | | | | |
| WATER WELL OWNER: USD #385 ANDOVER ATHLETIC FIELDS | | | Board of Agriculture, Division of Water Resource | | |
| RR#, ST. ADDRESS, BOX #: 1432 N. Andover Road | | | Application Number: | | |
| CITY, STATE, ZIP CODE: Andover, Kansas 67002 | | | | | |
| LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  | | 4 DEPTH OF COMPLETED WELL 140 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 02/16/2001 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 140 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No | | | |
| 5 | TYPE OF CASING USED: | | 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped | | |
| 1 | Steel | 3 RMP (SR) | 6 Asbestos-Cement | 9 Other (Specify below) Welded | |
| 2 | PVC | 4 ABS | 7 Fiberglass | SDR - 26 Threaded | |
| Blank casing Diameter 5 in. to 40 | | ft., Dia | in. to | ft., Dia | in. to ft. |
| Casing height above land surface 12 in., | | weight 2.35 | lbs./ft. | Wall thickness or gauge No. 10 Asbestos-cement .214 | |
| TYPE OF SCREEN OR PERFORATION MATERIAL: | | | | | |
| 1 | Steel | 3 Stainless Steel | 5 Fiberglass | 8 RMP (SR) | 11 other (specify) |
| 2 | Brass | 4 Galvanized steel | 6 Concrete tile | 9 ABS | 12 None used (open hole) |
| SCREEN OR PERFORATION OPENING ARE: | | | | | |
| 1 | Continous slot | 3 Mill slot | 5 Gauzed wrapped | 8 Saw cut 11 None (open hole) | |
| 2 | Louvered shutter | 4 Key punched | 6 Wire wrapped | 9 Drilled holes | |
| 3 | | | 7 Torch cut | 10 Other (specify) | |
| SCREEN-PERFORATION INTERVALS: from 40 ft. to 140 ft., From ft. to ft. | | | | | |
| GRAVEL PACK INTERVALS: from 24 ft. to 140 ft., From ft. to ft. | | | | | |
| 6 | GROUT MATERIAL: 1 Neat cement | | 2 Cement grout | 3 Bentonite | 4 Other bentonite hole plug |
| Grout Intervals: From 4 ft. to 24 | | ft. From | ft. to | ft. From 38 | ft. to 40 ft. |
| What is the nearest source of possible contamination: | | | | | |
| 1 | Septic tank | 4 Lateral lines | 7 Pit privy | 10 Livestock pens | 14 Abandon water well |
| 2 | Sewer lines | 5 Cess pool | 8 Sewage lagoon | 11 Fuel storage | 15 Oil well/Gas well |
| 3 | Watertight sewer lines | 6 Seepage pit | 9 Feedyard | 12 Fertilizer storage | 16 Other (specify below) |
| 13 Insecticide storage None Apparent | | | | | |
| Direction from well? How many feet? | | | | | |
| FROM | TO | LITHOLOGIC LOG | | FROM | TO |
| 0 | 3 | fill dirt | | | |
| 3 | 5 | rock | | | |
| 5 | 140 | shale | | | |
| 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 02/16/01 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 . This Water Well Record was completed on (mo/day/yr) 02/19/01 . Under the business name of Harp Well & Pump Service, Inc. by (signature) Todd S. Harp | | | | | |