

1 LOCATION OF WATER WELL: Fraction		Section Number		Township Number		Range Number	
County: Butler		SE 1/4 NW 1/4 SE 1/4		10		T 27 S R 4 E	
Distance and direction from nearest town or city street address of well if located within city?							
1 Mile N of Augusta Kans							
2 WATER WELL OWNER: Chuck Miller Olathe Kans 66062							
RR#, St. Address, Box # 15823 S. Abalony St Board of Agriculture, Division of Water Resources							
City, State, ZIP Code Application Number:							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:				4 DEPTH OF COMPLETED WELL: 127 ft. ELEVATION:			
				Depth(s) Groundwater Encountered 1. 95 ft. 2. ft. 3. ft.			
				WELL'S STATIC WATER LEVEL 35 ft. below land surface measured on mo/day/yr			
				Pump test data: Well water was ft. after hours pumping gpm			
				Est. Yield 45 gpm: Well water was ft. after hours pumping gpm			
				Bore Hole Diameter. 9 1/2 in. to ft., and in. to ft.			
				WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
				1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
				2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well			
				Was a chemical/bacteriological sample submitted to Department? Yes. No. X; If yes, mo/day/yr sample was submitted			
				Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:							
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued. X Clamped.							
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded							
7 Fiberglass Threaded.							
Blank casing diameter. 5 in. to ft., Dia in. to ft., Dia in. to ft.							
Casing height above land surface. 18 in., weight 160 lbs./ft. Wall thickness or gauge No. 214							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement							
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)							
12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes							
7 Torch cut 10 Other (specify) ft.							
SCREEN-PERFORATED INTERVALS: From 55 ft. to 127 ft. From ft. to ft.							
GRAVEL PACK INTERVALS: From ft. to ft. From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 3 ft. to 23 ft. From ft. to ft. From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well							
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well							
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)							
13 Insecticide storage							
Direction from well? N How many feet? 40							
FROM TO LITHOLOGIC LOG				FROM TO PLUGGING INTERVALS			
0 4 Soil							
4 25 Clay							
25 127 Shale & Lime							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/3/05 and this record is true to the best of my knowledge and belief. Kansas							
Water Well Contractor's Licence No. 251 This Water Well Record was completed on (mo/day/yr) 2/23/05							
under the business name of Winter Well Drill by (signature) Charles Winter							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.							