



1 LOCATION OF WATER WELL: County: Butler		Fraction NE 1/4 SW 1/4 NW 1/4	Section Number 27	Township Number T 27 S	Range Number R 4 E
Distance and direction from nearest town or city street address of well if located within city: The well is located approximately 420 feet south and 875 feet east of SW Thunder Rd and SW Dike Rd in Augusta. Latitude N37° 40'31.63" Longitude W96° 59'13.39"					
2 WATER WELL OWNER: Williams Petroleum Services, LLC					
RR#, St. Address, Box # : PO Box 3483		Board of Agriculture, Division of Water Resources Application Number: Not Applicable			
City, State, ZIP Code : Tulsa, Oklahoma 74101-3483					
3 LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL Depth(s) Groundwater Encountered 1 15 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 9.56 ft. below land surface measured on mo/day/yr 9/4/08 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 20 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) <input checked="" type="checkbox"/> 2 PVC 4 ABS		5 Wrought Iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass	CASING JOINTS: Glued Clamped Welded Threaded		
Blank casing diameter 2 in. to 15 ft., Dia		in. to ft., Dia	in. to ft., Dia	in. to ft.	
Casing height above land surface 26.4 in., weight 0.682 lbs./ft.			7 PVC 10 Asbestos-cement	Wall thickness or gauge No. 0.1875 in.	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 1 Continuous slot <input checked="" type="checkbox"/> 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 15 ft. to 20 ft.		From 15 ft. to 20 ft.	From 15 ft. to 20 ft.	From 15 ft. to 20 ft.	
GRAVEL PACK INTERVALS: From 13 ft. to 20 ft.		From 13 ft. to 20 ft.	From 13 ft. to 20 ft.	From 13 ft. to 20 ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals From 0 ft. to 13 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/ Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? W How many feet? approximately 30					
FROM	TO	CODE	LITHOLOGIC LOG	FROM	TO
0	10	03	Gray, silty clay		
10	15	02	Dark brown, clayey silt		
15	20	07	Reddish brown, fine sand, well sorted		
20	20	20	Fossiliferous limestone		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr) 8/5/08 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 616 This Water Well Record was completed on (mo/day/yr) 3/18/09 under the business name of Thiele Geotech, Inc. by (signature)  INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

SEC