


WATER WELL RECORD Form WWC-5 KSA 82a-1212

Form WWC-5 KSA 82a-121

1 LOCATION OF WATER WELL:		Fraction County: Butler SW $\frac{1}{4}$ SE $\frac{1}{4}$ SW $\frac{1}{4}$			Section Number 22	Township Number 27	Range Number R 4
Distance and direction from nearest town or city street address of well if located within city? 520 W. 7th St., Augusta, KS							
2 WATER WELL OWNER:		KDHE-BER			Board of Agriculture, Division of Water Resources		
RR#, St. Address, Box #		1000 SW Jackson; Ste. 410			Application Number:		
City, State, ZIP Code		Topeka, KS 66612					
3 LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX:					4 DEPTH OF COMPLETED WELL 20 ft. ELEVATION: 1221.84 Depth(s) Groundwater Encountered 1.5 15 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 11.94 ft. below land surface measured on mo/day/yr 04/23/13 Pump test data: Well water was ft. after hours pumping Gpm Est. Yield Gpm Well water was ft. after Hours pumping Gpm Bore Hole Diameter 6.5 in. to 20 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well MW-2R Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was Submitted Water Well Disinfected? Yes No X		
5 TYPE OF BLANK CASING USED:		5 Wrought Iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass			CASING JOINTS: Glued Welded Clamped Threaded X		
Blank casing diameter 2 in. to 10 ft., Dia							
Casing height above land surface FLUSH in. weight		SCH 40			Lbs./ft. Wall thickness or gauge No.		
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel 3 Stainless steel		5 Fiberglass			7 PVC 10 Asbestos-cement		
2 Brass 4 Galvanized steel		6 Concrete tile			8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot 3 Mill slot		5 Gauzed wrapped			8 Saw cut 11 None (open hole)		
2 Louvered shutter 4 Key punched		6 Wire wrapped			9 Drilled holes		
		7 Torch cut			10 Other (specify)		
SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft.					From		
SAND PACK INTERVALS: From 8 ft. to 20 ft.					From		
6 GROUT MATERIAL: 1 Neat cement		2 Cement grout		3 Bentonite		4 Other	
Grout Intervals From 2 0.5 ft. to 6 ft.		From 3 6 ft.		From 8 ft.		ft. to ft.	
What is the nearest source of possible contamination:							
1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens 14 Abandoned water well	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		11 Fuel storage 15 Oil well/ Gas well	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		12 Fertilizer storage 16 Other (specify below)	
Direction from well? How many feet?							
FROM	TO	CODE	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS
0	0.5	Asphalt					
0.5	2	Limestone					
2	20	Silty Clay					
20	TD	End of Borehole					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (x) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and w							
Completed on (mo/day/yr)		04/11/13		And this record is true to the best of my knowledge and belief. Kansas			
Water Well Contractor's License No.		585		This Water Well Record was completed on (mo/day/yr) 05/11/13			
under the business name of		Associated Environmental, Inc.		By (signature) Bradley J. Johnson			
INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.							