

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction County: Butler	SW $\frac{1}{4}$ SW $\frac{1}{4}$ NW $\frac{1}{4}$	Section Number 8	Township Number T 27 S	Range Number R 4 EW	
Distance and direction from nearest town, or city street address of well if located within city? 1 3/4 N. of 54 on 8th, Lake Rd.							
2 WATER WELL OWNER:		Donald Schmidt					Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :							Application Number:
City, State, ZIP Code :		RR, Augusta, KS.					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 60 ft. ELEVATION:					
		Depth(s) Groundwater Encountered 1 20 ft. 2. 40 ft. 3. ft.					
		WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr					
		Pump test data: Well water was ft. after hours pumping gpm					
		Est. Yield 8.5 gpm: Well water was ft. after hours pumping gpm					
		Bore Hole Diameter 10 in. to ft. and in. to ft.					
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well					
		Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted					
		Water Well Disinfected? Yes Yes No					
5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped <input type="checkbox"/>			
1 Steel		6 Asbestos-Cement	9 Other (specify below)	Welded <input type="checkbox"/>			
2 PVC		7 Fiberglass		Threaded <input type="checkbox"/>			
Blank casing diameter 5 in. to ft. , Dia in. to ft. , Dia in. to ft.							
Casing height above land surface 12 in., weight 160 lbs./ft. Wall thickness or gauge No.							
TYPE OF SCREEN OR PERFORATION MATERIAL:		PVC					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement		
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)		
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
1 Continuous slot		3 Mill slot	6 Wire wrapped	9 Drilled holes	12 None used (open hole)		
2 Louvered shutter		4 Key punched	7 Torch cut	10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From 40 ft. to 60 ft.	From 60 ft. to ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.
GRAVEL PACK INTERVALS:		From 20 ft. to 60 ft.	From 60 ft. to ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.
6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other		
Grout Intervals:		From 3 ft. to 20 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.		
What is the nearest source of possible contamination:							
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well		
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well		
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)		
13 Insecticide storage							
Direction from well?		How many feet? 80					
FROM	TO	LITHOLOGIC LOG			FROM	TO	LITHOLOGIC LOG
8	8	Earth					
8	14	Clay					
14	25	Grit Limestone					
25	45	Red Bed					
45	60	Gray Shale					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/21/85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 42 This Water Well Record was completed on (mo/day/yr) 9/26/85 under the business name of Reiser Well Drilling by (signature) Jerry Reiser CM							
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.							