


1 LOCATION OF WATER WELL: County: Butler		Fraction NW $\frac{1}{4}$ NW $\frac{1}{4}$ NE $\frac{1}{4}$	Section Number 22	Township Number T 27 S	Range Number R 41 EW
Distance and direction from nearest town or city street address of well if located within city? In City of Augusta					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code : 411 Harrington Kan		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: Depth(s) Groundwater Encountered 125 ft. ft. 2. ft. ft. 3. WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield 300 gpm Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No. If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (specify below)	CASING JOINTS: Glued X Clamped Welded Threaded	
Blank casing diameter 5 in. to 20 ft. Dia in. to ft. Dia in. to ft.		Casing height above land surface 18 in. weight 160 lbs./ft. Wall thickness or gauge No. 1214			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 7 Torch cut 8 Saw cut 11 None (open hole) 9 Drilled holes 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 20 ft. to 41 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft. From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 10 Insecticide storage					
Direction from well? N How many feet? 200					
FROM 0 4 10 20	TO 4 10 20 41	LITHOLOGIC LOG 50' L Clay Clay & Shale Shale-Gravel-Lime	FROM	TO	PLUGGING INTERVALS
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/30/91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 57 This Water Well Record was completed on (mo/day/yr) 12/30/91 under the business name of Winter Well Drill by (signature) Charles R. Winter					