

1 LOCATION OF WATER WELL:	Fraction County: POTTER	Section Number SW $\frac{1}{4}$ SW $\frac{1}{4}$ SW $\frac{1}{4}$	Township Number T 27 S	Range Number R 40 E/W	
Distance and direction from nearest town or city street address of well if located within city? 60 W 7th AUGUSTA KS					
2 WATER WELL OWNER:	COASTAL				
RR#, St. Address, Box #	60 W 7th				
City, State, ZIP Code	AUGUSTA KS				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:					
4 DEPTH OF COMPLETED WELL:	19 ft. ELEVATION:				
Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. ft.					
WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr					
Pump test data: Well water was ft. after hours pumping gpm					
Est. Yield gpm: Well water was ft. after hours pumping gpm					
Bore Hole Diameter 8 in. to 19 ft. and in. to ft.					
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No. If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No					
5 TYPE OF BLANK CASING USED:	Casing Joints: Glued Clamped				
1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	9 Other (specify below)	
PVC	4 ABS	6 Asbestos-Cement	7 Fiberglass	Welded Threaded	
Blank casing diameter 2 in. to 9 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface in., weight				lbs./ft. Wall thickness or gauge No.	
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC				
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement	
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)	
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut				
1 Continuous slot	3 Mill slot	9	19	8 Saw cut 9 Drilled holes 10 Other (specify)	
2 Louvered shutter	4 Key punched				
SCREEN-PERFORATED INTERVALS:	From 9 ft. to 19 ft.	ft. to 19 ft.	ft. to 19 ft.	ft. to 19 ft.	
GRAVEL PACK INTERVALS:	From 8 ft. to 19 ft.	ft. to 19 ft.	ft. to 19 ft.	ft. to 19 ft.	
6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other	
Grout Intervals:	From 5 ft. to 8 ft.	From 5 ft. to 8 ft.	From 5 ft. to 8 ft.	From 5 ft. to 8 ft.	
What is the nearest source of possible contamination:	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage				
1 Septic tank	4 Lateral lines	7 Pit privy	8 Sewage lagoon	14 Abandoned water well	
2 Sewer lines	5 Cess pool	9 Feedyard		15 Oil well/Gas well	
3 Watertight sewer lines	6 Seepage pit			16 Other (specify below)	
Direction from well?	WITHIN STATION				
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	12	C-TAB			
12 TD		SAND			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:	This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/1/92 and this record is true to the best of my knowledge and belief. Kansas				
Water Well Contractor's License No. 102	This Water Well Record was completed on (mo/day/yr) 7/1/92				
under the business name of LANE WESTERN CO	by (signature) R. Moore				