

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: BUTLER	SE 1/4 SW 1/4 SW 1/4	22	T 27 S	R 4 EW

Distance and direction from nearest town or city street address of well if located within city?

520 W 7TH AUGUSTA KS

2 WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #:	Application Number:
MCDONALD CORP.	
11880 COLLEGE BOULEVARD - SUITE 500	
City, State, ZIP Code:	
OVERLAND PARK KS 66210	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 25 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 18.9 ft. 2. — ft. 3. — ft.
	WELL'S STATIC WATER LEVEL 17.06 ft. below land surface measured on mo/day/yr 05-16-94
	Pump test data: Well water was — ft. after — hours pumping — gpm
	Est. Yield — gpm: Well water was — ft. after — hours pumping — gpm
	Bore Hole Diameter: 8.125 in. to 25 ft. and — in. to — ft.
WELL WATER TO BE USED AS:	
5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes — No X ; If yes, mo/day/yr sample was submitted —	
Water Well Disinfected? Yes — No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued — Clamped —
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded —
Blank casing diameter 2 in. to 10 ft. Dia — in. to — ft. Dia — in. to — ft.			Threaded X
Casing height above land surface FLUSH in., weight SC 40 lbs./ft. Wall thickness or gauge No. —			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	11 None (open hole)
SCREEN-PERFORATED INTERVALS:			
From 10 ft. to 20 ft. From — ft. to — ft.			
From — ft. to — ft. From — ft. to — ft.			
GRAVEL PACK INTERVALS:			
From 8.5 ft. to 25 ft. From — ft. to — ft.			
From — ft. to — ft. From — ft. to — ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0.5 ft. to 6.5 ft. From 6.5 ft. to 8.5 ft. From — ft. to — ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
CONTAMINATED SITE				
Direction from well? —				
How many feet? —				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.5	1.5	ASPHALT			
1.5	1	CONCRETE			
1	13	SILTY CLAY			
13	15	SANDY CLAY			
15	22	SILTY SAND			
22	25	LIMESTONE GRAVEL & SAND			
TD	25				

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 05-11-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 06-10-94 under the business name of EBBERTS DRILLING by (signature) [Signature]
