

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: BUTLER	SE 1/4 SW 1/4 SW 1/4	22	T 27 S	R 4 EW

Distance and direction from nearest town or city street address of well if located within city?

520 W 7TH AGOSTA KS.

2 WATER WELL OWNER:	MCDONALD CORP	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #:	1188D COLLEGE BOULEVARD - SUITE 500	Application Number:
City, State, ZIP Code:	OVERLAND PARK KS 66210	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 25 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 22 ft. 2. — ft. 3. — ft. WELL'S STATIC WATER LEVEL 13.24 ft. below land surface measured on mo/day/yr 05-16-94 Pump test data: Well water was — ft. after — hours pumping — gpm Est. Yield — gpm: Well water was — ft. after — hours pumping — gpm Bore Hole Diameter 8.625 in. to 25 ft., and — in. to — ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes — No X ; If yes, mo/day/yr sample was submitted — Water Well Disinfected? Yes — No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued — Clamped —
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	11 Injection well
Blank casing diameter 2 in. to 10 ft., Dia — in. to — ft., Dia — in. to — ft.			Welded —
Casing height above land surface FLUSH in., weight SCH 40 lbs./ft. Wall thickness or gauge No. —			Threaded X
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft., From — ft. to — ft., From — ft. to — ft.			
SAID			
GRAVEL PACK INTERVALS: From 9 ft. to 25 ft., From — ft. to — ft., From — ft. to — ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other —
Grout Intervals: From 5L ft. to 7 ft., From — ft. to — ft., From — ft. to — ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well? —				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				CONTAMINATED SITE
				How many feet? —

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
GL	1	ASPHALT- GRAVEL			
1	4	FILL - SILT + CLAY			
4	18	SILTY CLAY			
18	22	CLAY SILT			
22	25	SILTY SAND w- GRAVEL			
TD	25				

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 05-11-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 05-10-94 under the business name of EBBERTS DRILLING by (signature) <i>Gregory Ebberts</i>
