


1 LOCATION OF WATER WELL:		Fraction SW 1/4 NE 1/4 SW 1/4	Section Number 27	Township Number T 27 S	Range Number R 4 EW
Distance and direction from nearest town or city street address of well if located within city?					
2 WATER WELL OWNER: Mobil Oil Corporation					
RR#, St. Address, Box # : P.O. Box 246			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Beaumont, TX 77704			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 25 ft. ELEVATION: 1191.4			
<div style="text-align: center;"></div>		Depth(s) Groundwater Encountered 1. 13 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 6.3 ft. below land surface measured on mo/day/yr 7/17/85			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter 6 in. to 25 ft., and in. to ft.		WELL WATER TO BE USED AS:			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		5 Public water supply 8 Air conditioning 11 Injection well			
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well					
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No X					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued Clamped			
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)		Welded			
Blank casing diameter 2.4 in. to 25 ft., Dia in. to ft., Dia in. to ft.		Threaded X			
Casing height above land surface 30 in., weight lbs./ft. Wall thickness or gauge No. 0.2"					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)		9 Drilled holes			
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 5 ft. to 25 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 2.5 ft. to 25 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Cement-bentonite					
Grout Intervals: From ft. to ft., 3 From 1.3 ft. to 2.5 ft., 4 From 0 ft. to 1.3 ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well		11 Fuel storage 15 Oil well/Gas well			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)		13 Insecticide storage Hydrocarbons			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	27	Silty Clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/11/85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 399 This Water Well Record was completed on (mo/day/yr) 8/21/85 under the business name of Woodward-Clyde Consultants by (signature) Robert G. Michael					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					