


1 LOCATION OF WATER WELL:		Fraction County: Butler	NW $\frac{1}{4}$ SW $\frac{1}{4}$ SE $\frac{1}{4}$	Section Number 27	Township Number T 27 S	Range Number R 4 E
Distance and direction from nearest town or city street address of well if located within city? <i>South edge of Augusta</i>						
2 WATER WELL OWNER:		Mob 01 01 Corporation RR#, St. Address, Box # : P.O. Box 246, Gulf States Rd.		Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 28.0 ft. ELEVATION: 1220 Depth(s) Groundwater Encountered 1 9.0 ft. 2 ft. 3 ft.				
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12.0 in. to 30.0 ft., and in. to ft.				
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well				
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No		
5 TYPE OF BLANK CASING USED:		5 Wrought iron 1 Steel 2 PVC	8 Concrete tile 6 Asbestos-Cement 4 ABS	CASING JOINTS: Glued Welded Clamped Threaded		
Blank casing diameter 4.0 in. to 2.5 ft., Dia in. to ft., Dia in. to ft.						
Casing height above land surface 18.0 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40						
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC		10 Asbestos-cement 11 Other (specify) 12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 1 Continuous slot 2 Louvered shutter	8 RMP (SR) 3 Mill slot 4 Key punched	9 ABS	10 Other (specify)	11 None (open hole)
SCREEN-PERFORATED INTERVALS: From 2.5 ft. to 27.5 ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From 2.0 ft. to 28.0 ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement Grout Intervals: From 0 ft. to 2.0 ft., From ft. to ft., From ft. to ft., From ft. to ft.		2 Cement grout	3 Bentonite	4 Other		
What is the nearest source of possible contamination:				10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) Oil Refinery	
1 Septic tank 2 Sewer lines 3 Watertight sewer lines		4 Lateral lines 5 Cess pool 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard	How many feet? 1000'		
Direction from well?						
FROM	TO	LITHOLOGIC LOG		FROM	TO	LITHOLOGIC LOG
0	2.0	Topsoil, concrete and rock FILL				
2.0	7.0	Brown, CLAY				
7.0	29.0	Brown and gray CLAY				
29.0	32.0	Gray, CLAY with sand				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/16/86 and this record is true to the best of my knowledge and belief. Kansas						
Water Well Contractor's License No. 399 This Water Well Record was completed on (mo/day/year) 12/24/86						
under the business name of Woodward-Clyde Consultants by (signature) <i>Richard J. McGehee</i>						

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.