


1 LOCATION OF WATER WELL:		Fraction County: Butler	SE 1/4	SW 1/4	SW 1/4	Section Number 27	Township Number T 27 S	Range Number R 4 EW
Distance and direction from nearest town or city street address of well if located within city? <i>South edge of Augusta</i>								
2 WATER WELL OWNER:		Mobile Oil Corporation P.O. Box 246, Gulf States Rd.			Board of Agriculture, Division of Water Resources Application Number:			
City, State, ZIP Code		Beaumont, TX 77704-0246						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:					4 DEPTH OF COMPLETED WELL 24.0 ft. ELEVATION: 1220 Depth(s) Groundwater Encountered 1. 19.0 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter. 12.0 in. to 24.0 ft. and. in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes.....No. X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes Yes No			
5 TYPE OF BLANK CASING USED:		1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped		
		2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded Threaded		
Blank casing diameter	 4.0 in. to 3.5 ft., Dia in. to ft., Dia in. to ft. lbs./ft. Wall thickness or gauge No.	Schedule 40		
Casing height above land surface	 18.0 in., weight						
TYPE OF SCREEN OR PERFORATION MATERIAL:		1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement		
		2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)		
SCREEN OR PERFORATION OPENINGS ARE:		1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)		
		2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes			
SCREEN-PERFORATED INTERVALS:		From. 3.5 ft. to 23.5 ft., From	From ft. to ft., From	From ft. to ft., From	From ft. to ft., From	ft. to ft.		
GRAVEL PACK INTERVALS:		From. 3.0 ft. to 24.0 ft., From	From ft. to ft., From	From ft. to ft., From	From ft. to ft., From	ft. to ft.		
6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other			
Grout Intervals:		From. 0 ft. to 3.0 ft., From ft. to ft., From ft. to ft., From ft. to ft., From	ft. to ft.		
What is the nearest source of possible contamination:								
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well			
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well			
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)			
Direction from well?								
FROM	TO	LITHOLOGIC LOG			FROM	TO	LITHOLOGIC LOG	
0	5.0	Black-dark brown Silty CLAY						
5.0	22.0	Gray Silty CLAY						
22.0	25.5	Gray-green Silty CLAY with trace of sand						
25.5	26.0	Medium grained SAND with trace of silt						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/19/86 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 399 This Water Well Record was completed on (mo/day) 12/24/86 under the business name of Woodward-Clyde Consultants by (signature) <i>Richard M. Nichols</i> INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.								