

1 LOCATION OF WATER WELL:		Fraction County: Butler 008 SE $\frac{1}{4}$ SW $\frac{1}{4}$ SW $\frac{1}{4}$	Section Number T 27 S 22	Township Number R 4 E N	Range Number	
Distance and direction from nearest town or city street address of well if located within city? In town						
2 WATER WELL OWNER:		Coastal Mart				Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #:		610 W. 7th				Application Number:
City, State, ZIP Code:		Augusta, Ks.				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 14' ft. ELEVATION:				
		Depth(s) Groundwater Encountered 1 ft. ft. 2 ft. ft. 3 ft.				
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr				
		Pump test data: Well water was ft. after hours pumping gpm				
		Est. Yield gpm: Well water was ft. after hours pumping gpm				
		Bore Hole Diameter 8'6" in. to 14' ft. and in. to ft.				
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well				
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)				
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well				
		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted				
		Water Well Disinfected? Yes No				
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped				
1 Steel 3 RMP (SR) 4 ABS		6 Asbestos-Cement 9 Other (specify below)				
2 PVC		7 Fiberglass				
Blank casing diameter 4.500 in. to 8'3"		ft. Dia in. to ft. Dia in. to ft.				
Casing height above land surface. Flush Mount in., weight						
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 8 BMP (SR)				
1 Steel 3 Stainless steel 2 Brass 4 Galvanized steel		5 Fiberglass 6 Concrete tile 9 ABS				
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 6 Wire wrapped 7 Torch cut				
1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched		8 Saw cut 9 Drilled holes 10 Other (specify)				
SCREEN-PERFORATED INTERVALS: From 13'5" ft. to 8'5" ft. From ft. to ft. From ft. to ft.						
GRAVEL PACK INTERVALS: From 14'0" ft. to 4'3" ft. From ft. to ft. From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		10 Livestock pens 14 Abandoned water well				
Grout Intervals: From 4'3" ft. to 2'3" ft. From 2'3" ft. to 0 ft. From 0 ft. to ft.		11 Fuel storage 15 Oil well/Gas well				
What is the nearest source of possible contamination:		12 Fertilizer storage 16 Other (specify below)				
1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit		13 Insecticide storage				
Direction from well? North		How many feet? 3'				
FROM TO LITHOLOGIC LOG		FROM TO	PLUGGING INTERVALS			
0	1	Concrete w/ sand underlayment				
1	5	Dk gray silty clay fill w/ ls. rx. rubble, asphalt concrete rubble, odor.				
5	12	Olive gray-dk gray tight silty clay, moist, odor.				
12	14'	Gray brn-brn sandy silt to sandy clay, moist, odor, mottled.				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-29-94 and this record is true to the best of my knowledge and belief. Kansas						
Water Well Contractor's License No. 539 under the business name of JB Environmental Drilling		This Water Well Record was completed on (mo/day/yr) 1-2-95 by (signature) James Bueker				
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						