

1 LOCATION OF WATER WELL		Fraction	Section Number	Township Number	Range Number
County: <u>Butler</u>		<u>NW 1/4 SW 1/4 SW 1/4</u>	<u>16</u>	<u>T 27 S</u>	<u>R 5 EW</u>
Distance and direction from nearest town or city? <u>5 E 1 N Augusta</u>			Street address of well if located within city?		
2 WATER WELL OWNER: <u>Wayne Robinson</u>					
RR#, St. Address, Box # : <u>R 2 Augusta 67010</u>			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code			Application Number:		
3 DEPTH OF COMPLETED WELL <u>100</u> ft. Bore Hole Diameter <u>8</u> in. to <u>100</u> ft., and in. to ft.					
Well Water to be used as:					
1 Domestic		3 Feedlot	5 Public water supply	8 Air conditioning	11 Injection well
2 Irrigation		4 Industrial	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
		7 Lawn and garden only	10 Observation well		
Well's static water level <u>45</u> ft. below land surface measured on <u>3</u> month <u>6</u> day <u>7</u> year					
Pump Test Data: Well water was <u>100</u> ft. after <u>1</u> hours pumping <u>Bailing 400 GPH</u> gpm					
Est. Yield <u>400 GPH</u> gpm. Well water was ft. after hours pumping gpm					
4 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	Casing Joints: Glued ☒ Clamped
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
			7 Fiberglass		Threaded
Blank casing dia <u>6</u> in. to ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface <u>18</u> in., weight lbs./ft. Wall thickness or gauge No <u>175</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
				9 ABS	12 None used (open hole)
Screen or Perforation Openings Are:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
Screen-Perforation Dia <u>6</u> in. to <u>100</u> ft., Dia in. to ft., Dia in. to ft.					
Screen-Perforated Intervals: From <u>60</u> ft. to <u>100</u> ft., From ft. to ft., From ft. to ft.					
Gravel Pack Intervals: <u>None</u> From ft. to ft., From ft. to ft., From ft. to ft.					
5 GROUT MATERIAL:					
1 Neat cement		2 Cement grout	3 Bentonite	4 Other	
Grouted Intervals: From <u>0</u> ft. to <u>10</u> ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Cess pool	7 Sewage lagoon	10 Fuel storage	14 Abandoned water well
2 Sewer lines		5 Seepage pit	8 Feed yard	11 Fertilizer storage	15 Oil well/Gas well
3 Lateral lines		6 Pit privy	9 Livestock pens	12 Insecticide storage	16 Other (specify below)
Direction from well <u>N E</u> How many feet <u>200</u> ? Water Well Disinfected? ☒ Yes ☐ No					
Was a chemical/bacteriological sample submitted to Department? Yes ☐ No ☒ If yes, date sample was submitted month day year Pump Installed? Yes ☐ No ☒					
If Yes: Pump Manufacturer's name Model No. HP Volts					
Depth of Pump Intake ft. Pumps Capacity rated at gal./min.					
Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other					
6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on <u>3</u> month <u>0</u> day <u>27</u> year					
and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>251</u>					
This Water Well Record was completed on month <u>23</u> day <u>1980</u> year under the business name of <u>Winter Well Drilling</u> by (signature) <u>Charles W. Winters</u>					
7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG	
		0 1 Soil			
		1 30 Rock			
		30 40 Clay yellow			
		40 55 Shale			
		55 100 LIME			
ELEVATION:		Signature on file			
Depth(s) Groundwater Encountered 1. <u>70</u> ft. 2. ft. 3. ft. 4. ft. (Use a second sheet if needed)					

OFFICE USE ONLY

T

2

7

R

5

EW

SEC

16

NW 1/4

SW 1/4

SW 1/4

SW 1/4

SW 1/4

SW 1/4

SW 1/4

SW 1/4

SW 1/4