

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Butler		NW 1/4 SE 1/4 SW 1/4	20	T 27 S	R 5 E/W
Distance and direction from nearest town or city street address of well if located within city? 3 mi. E of Augusta					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # : 2721 Box 232 E		Application Number:			
City, State, ZIP Code : Augusta, KS 67010					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 140 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 120 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr 5/15/93			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 50 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 10 in. to ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) ☐ Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued ☒ Clamped			
1 Steel 3 RMP (SR)		8 Concrete tile 9 Other (specify below)			
☒ 2 PVC 4 ABS		7 Fiberglass Welded			
Blank casing diameter 5 in. to ft. Dia. in. to ft. Dia. in. to ft.		Threaded			
Casing height above land surface 12 in., weight 160 lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot ☒ 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify)			
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS: From 120 ft. to 140 ft. From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 20 ft. to 140 ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout ☒ 3 Bentonite 4 Other					
Grout Intervals: From 3 ft. to 20 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool ☒ Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well? Downslope		How many feet? 50+			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	DIRT			
4	25	SANDY CLAY			
25	42	grey shale			
42	44	Red bed			
44	76	Shaley lime			
76	79	red bed			
79	140	Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/15/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 1493 This Water Well Record was completed on (mo/day/yr) under the business name of Reiserer Well Drilling by (signature) <i>[Signature]</i>					