

1 LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 NW 1/4 Section Number 29 Township Number T 27 S Range Number R 6 E
 County: BUTLER
 Distance and direction from nearest town or city street address of well if located within city? 3/4 mile West of Leon on 96 highway South Side

2 WATER WELL OWNER: BOB PATTERSON EXISTING
 RR#, St. Address, Box #: Box 326
 City, State, ZIP Code: LEON, KS 67074
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 200 ft. ELEVATION: 40 ft.

Depth(s) Groundwater Encountered 1 40 ft. 2 40 ft. 3 40 ft.
 WELL'S STATIC WATER LEVEL 40 ft. below land surface measured on mo/day/yr MAY 7 1989
 Pump test data: Well water was existing ft. after 5 hours pumping 30 gpm
 Est. Yield 30 gpm: Well water was existing ft. after 5 hours pumping 30 gpm
 Bore Hole Diameter 5 in. to 5 ft. and 5 in. to 5 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well
 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) ABR
 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes Yes No No If yes, mo/day/yr sample was submitted Yes Water Well Disinfected Yes No No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped Welded
2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Threaded Threaded
 Blank casing diameter 5 in. to 5 ft. Dia. 5 in. to 5 ft. Dia. 5 in. to 5 ft.
 Casing height above land surface +12 in., weight 200 lbs./ft. Wall thickness or gauge No. 200

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 7 PVC
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Baled holes
 7 Torch cut 10 Other (specify) 8 Saw cut

SCREEN-PERFORATED INTERVALS: From 100 ft. to 200 ft. From 200 ft. to 200 ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 200 ft. From 200 ft. to 200 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 20 ft. From 20 ft. to 20 ft. From 20 ft. to 20 ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? Downslope How many feet? +50

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		existing Cased well Baled out and Cleaned, pulled steel pipe and replaced with PVC			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) MAY 7 1989 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 493 This Water Well Record was completed on (mo/day/yr) June 28, 89 under the business name of Raisers Well Drilling by (signature) Jerry Reimer