

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SE		SE 1/4 NW 1/4 NW 1/4	34	T 27 S	R 7E EW
Distance and direction from nearest town or city street address of well if located within city? 7 MILES EAST OF LEON ON HIGHWAY 96 MWSB5					
2 WATER WELL OWNER: MCCONNELL AFB C/O TETRA TECH INC.					
RR#, St. Address, Box #: 10 E. CAMBRIDGE CIR. DR., STE 130					
City, State, ZIP Code: KANSAS CITY, KS 66103					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 88.0 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 70.0 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 70 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8.75 in. to 88.0 ft. and in. to ft.			
WELL WATER TO BE USED AS:					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 4" in. to 73.0 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 6 in. weight lbs./ft. Wall thickness or gauge No. Sch 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 73.0 ft. to 83.0 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 70.0 ft. to 83.0 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 3/8" HOLE PLUG 5 SAND					
Grout Intervals: From 0.0 ft. to 65.0 ft. From 65.0 ft. to 73.0 ft. From 83.0 ft. to 88.0 ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	34.0	BROWN CLAY & LIMESTONE WICHURT FILL MATERIAL			
34.0	50.0	LIMESTONE - WET			
50.0	88.0	SHALE & LIMESTONE LAYERS			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-28-95 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 551 This Water Well Record was completed on (mo/day/yr) 11-18-96					
under the business name of Associated Environmental Industries by (signature)					