


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: BUTLER	SE 1/4 NW 1/4 NW 1/4	34	T 27 S	R 7E EW

Distance and direction from nearest town or city street address of well if located within city?

7 MILES EAST OF ~~LOMA~~ ON HIGHWAY 96

MWSB4

2 WATER WELL OWNER:	RR#, St. Address, Box #	Board of Agriculture, Division of Water Resources
McCONNELL AFB C/O TETRA TECH INC.	10E. CAMBRIDGE CIR. DR., STE. 130	
City, State, ZIP Code	KANSAS CITY, KS 66103	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	ft. ELEVATION:
	34.0	22.0
	Depth(s) Groundwater Encountered 1. 14.0 ft. 2. 22.0 ft. 3. ft.	
	WELL'S STATIC WATER LEVEL 14 ft. below land surface measured on mo/day/yr	
	Pump test data: Well water was ft. after hours pumping gpm	
	Est. Yield gpm: Well water was ft. after hours pumping gpm	
	Bore Hole Diameter 8.75 in. to 34.0 ft. and in. to ft.	
	WELL WATER TO BE USED AS:	
	5 Public water supply 8 Air conditioning 11 Injection well	
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
	Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted	
	Water Well Disinfected? Yes No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 4 in. to 23.75 ft. Dia			Threaded X
Casing height above land surface 0 in. weight lbs./ft. Wall thickness or gauge No. Sch 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:	1 Steel	3 Stainless steel	5 Fiberglass
	2 Brass	4 Galvanized steel	6 Concrete tile
SCREEN OR PERFORATION OPENINGS ARE:	1 Continuous slot	2 Mill slot	3 Gauzed wrapped
	4 Louvered shutter	4 Key punched	6 Wire wrapped
SCREEN-PERFORATED INTERVALS:	From 23.75 ft. to 33.75 ft.		
	From 18.0 ft. to 34.0 ft.		
GRAVEL PACK INTERVALS:	From 18.0 ft. to 34.0 ft.		
	From ft. to ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other 3/8" HOLE PLUG
Grout Intervals: From 0.0 ft. to 16.0 ft. From 16.0 ft. to 18.0 ft. From ft. to ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well?				How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	22.0	BROWN CLAY W/LIMESTONE AND SHALE - CHURT FILL MATERIAL			
22.0	34.0	TAN SILTY SAND - WET/SCFT			
34.0	34.0	HARD LIMESTONE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-15-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 551 This Water Well Record was completed on (mo/day/yr) 11-15-96 under the business name of ASSOCIATED ENVIRONMENTAL INDUSTRIES by (signature)
