


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County Butler	Fraction NW 1/4 SE 1/4 NW 1/4	Section number 23	Township number T 27	Range number S R 7 E E/W
2. Distance and direction from nearest town or city: 8 miles E of Leon			3. Owner of well: Four Winds Girl Scout		
Street address of well location if in city:			R.R. or street: R.R.		
City, state, zip code: Leon, E1 dorado, Ks 67042					
4. Locate with "X" in section below:		Sketch map:			
					
5. Type and color of material		From	To	6. Bore hole 10 3/4 in. Completion date 8-15-77	
Flint Gravel (all sizes)		0	3'	Well depth 220 ft.	
Brown Clay		3'	6'	7. ☒ Cable tool ☐ Rotary ☐ Driven ☐ Dug	
Red Schale		6'	23'	☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary	
Yellow Clay		23'	32'	8. Use: ☒ Domestic ☐ Public supply ☐ Industry	
Yellow Schale		32'	39'	☐ Irrigation ☐ Air conditioning ☐ Stock	
Blue Schale		39'	53'	☐ Lawn ☐ Oil field water ☐ Other	
Hard Blue Schale		53'	58'	9. Casing: Material RMP Height: Above or below	
Red Clay		58'	65'	Threaded ☐ Welded ☐ Surface 16 in.	
Hard Gray Schale		65'	85'	RMP ☒ PVC ☐ Weight 195 lbs./ft.	
Hard Sandstone (Cream)		85'	101'	Dia. 6 in. to 220 ft. depth Wall Thickness: inches or	
Blue Schale		101'	109'	Dia. 6 in. to 220 ft. depth gage No. 200	
Red Bed Clay		109'	120'	10. Screen: Manufacturer's name Sunflower	
Lime		120'	122'	Type RMP Dia. 6"	
Broken Lime & Schale		122'	125'	Slot/gauze 1/16 Length 40'	
Blue Schale		125'	138'	Set between 180 ft. and 220 ft.	
				Gravel pack? Yes Size range of material 1/4" SAND	
				11. Static water level: 75 ft. below land surface Date 8-12-77	
				12. Pumping level below land surfaces: NA	
				13. Water sample submitted: Yes ☒ No ☐ Date	
				14. Well head completion: Yes	
				☒ Pitless adapter 16 inches above grade	
				15. Well grouted? No	
				With: ☐ Neat cement ☐ Bentonite ☐ Concrete	
				Depth: From 100 ft. to EAST Type Sewer	
				16. Nearest source of possible contamination: EAST Type Sewer	
				Well disinfected upon completion? ☒ Yes ☐ No	
				17. Pump: Pumpco Not installed	
				Manufacturer's name	
				Model number Sub HP 1 Volts 230	
				Length of drop pipe 150 ft. capacity 10 g.p.m.	
				Type:	
				☒ Submersible ☐ Turbine	
				☐ Jet ☐ Reciprocating	
				☐ Centrifugal ☐ Other	
18. Elevation:	19. Remarks:		20. Water well contractor's certification:		
Topography:	To be grouted & cement slab made by caretaker (This well is for caretaker's house only)		This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
☐ Hill			EASTMAN Drilling		
☒ Slope			Business name Box 115, Winfield License No.		
☒ Upland			Address Box 115, Winfield		
☐ Valley			Signed Dale Eastman Date 8-15-77		
			Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

