

1 LOCATION OF WATER WELL:		FRACTION		Section Number		Township Number		Range Number	
Sedgwick		NW SE SW SW NE 1/4 SE 1/4 SW 1/4		31		T 28 S		R 1E F/W	

Distance and direction from nearest town or city street address of well if located within city?

133 Timber Lane Haysville, Kansas

2	WATER WELL OWNER:	KOONTZ, J.R.	Board of Agriculture, Division of Water Resource
	RR#, ST. ADDRESS, BOX #:	133 Timber Lane	
	CITY, STATE, ZIP CODE:	Haysville, Kansas	
			Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 60 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 35 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 04/08/1996 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 60 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; if yes, mo/day/yr sample was submitted Water Well Disinfected? Yes Y No
---	--

5 TYPE OF CASING USED:		3 Wrought iron		8 Concrete tile		CASING JOINTS:		Glued ☒ Clamped	
1 Steel		6 Asbestos-Cement		9 Other (Specify below)				Welded	
2 PVC		7 Fiberglass		SDR-26				Threaded	
Blank casing Diameter 5 in. to 40		ft., Dia		in. to		ft., Dia		in. to	
Casing height above land surface 12 in.		weight 2.35		lbs. / ft.		Wall thickness or gauge No.		.214	
TYPE OF SCREEN OR PERFORATION MATERIAL:		5 Fiberglass		7 PVC		10 Asbestos-cement			
1 Steel		3 Stainless Steel		8 RMP (SR)		11 other (specify)			
2 Brass		4 Galvanized steel		9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENING ARE:		5 Gauzed wrapped		8 Saw cut		11 None (open hole)			
1 Continous slot		6 Wire wrapped		9 Drilled holes					
2 Louvered shutter		7 Torch cut		10 Other (specify)					
SCREEN-PERFORATION INTERVALS:		from 40		ft. to 60		ft., From		ft. to	
		from		ft. to		ft., From		ft. to	
GRAVEL PACK INTERVALS:		from 24		ft. to 60		ft., From		ft. to	
		from		ft. to		ft., From		ft. to	

6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 4		ft. to 24	ft. From	ft. to	ft. From
What is the nearest source of possible contamination:					
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandon water well	
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well	
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)	
			13 Insecticide storage		

Direction from well? **West** How many feet? **18**

[illegible]

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 04/08/1996 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 04/09/96 Under the business name of Harp Well & Pump Service, Inc by (signature)

Jane Frederick