


mw-5

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction SW $\frac{1}{4}$ NE $\frac{1}{4}$ NW $\frac{1}{4}$	Section Number 11	Township Number T 28 S	Range Number R 1 E/W																																																
Distance and direction from nearest town or city street address of well if located within city? 3232 S. Clifton, Wichita, Kansas																																																					
2 WATER WELL OWNER: RR#, St. Address, Box # Novinger Co. City, State, ZIP Code 3232 S. Clifton, Wichita, Ks 67512 Board of Agriculture, Division of Water Resources Application Number: _____																																																					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 33 ft. ELEVATION: _____ Depth(s) Groundwater Encountered 1. _____ ft. 2. _____ ft. 3. _____ ft. WELL'S STATIC WATER LEVEL _____ ft. below land surface measured on 11/10/96 day/yr Pump test data: Well water was _____ ft. after _____ hours pumping _____ gpm Est. Yield _____ gpm: Well water was _____ ft. after _____ hours pumping _____ gpm Bore Hole Diameter: 8.625 in. to 33 ft., and _____ in. to _____ ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well mw-5 Was a chemical/bacteriological sample submitted to Department? Yes _____ No X If yes, mo/day/yr sample was submitted _____ Water Well Disinfected? Yes _____ No X																																																			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued _____ Clamped _____ 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded _____ Blank casing diameter 2 in. to 18 ft., Dia _____ in. to _____ ft., Dia _____ in. to _____ ft. Casing height above land surface _____ in., weight SCH 40 PVC lbs./ft. Wall thickness or gauge No. _____ TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) _____ 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) _____ SCREEN-PERFORATED INTERVALS: From 18 ft. to 33 ft., From _____ ft. to _____ ft. GRAVEL PACK INTERVALS: From 17 ft. to 33 ft., From _____ ft. to _____ ft.																																																					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other _____ Grout Intervals: From 20 ft. to 15 ft., From 15 ft. to 17 ft., From _____ ft. to _____ ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Contaminated Si Direction from well? _____ How many feet? _____																																																					
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>GL</td> <td>2.00</td> <td>Grass and topsoil</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>2.00 14.00</td> <td>Dark brown, silty clay</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>14.00 24.00</td> <td>Lt brown, fine sand and silt</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>24.00 32.00</td> <td>Red brown coarse sand</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>32.00 33.00</td> <td>white, fine, sand</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>33.00 TD</td> <td>End of Borehole</td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="6" style="height: 100px; vertical-align: bottom; text-align: right;"> Flush Mount waiver D. Taylor 7/2/96 </td> </tr> </tbody> </table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	GL	2.00	Grass and topsoil					2.00 14.00	Dark brown, silty clay					14.00 24.00	Lt brown, fine sand and silt					24.00 32.00	Red brown coarse sand					32.00 33.00	white, fine, sand					33.00 TD	End of Borehole				Flush Mount waiver D. Taylor 7/2/96					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																
GL	2.00	Grass and topsoil																																																			
	2.00 14.00	Dark brown, silty clay																																																			
	14.00 24.00	Lt brown, fine sand and silt																																																			
	24.00 32.00	Red brown coarse sand																																																			
	32.00 33.00	white, fine, sand																																																			
	33.00 TD	End of Borehole																																																			
Flush Mount waiver D. Taylor 7/2/96																																																					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, 2 reconstructed, or 3 plugged under my jurisdiction and was completed on (mo/day/year) 7/11/96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 585 This Water Well Record was completed on (mo/day/yr) 8/10/96 under the business name of Associated Environmental, Inc. by (signature) <i>[Signature]</i>																																																					