

1 LOCATION OF WELL: 2801 S. Hydraulic, Wichita, KS		Fraction NW NW SW	Section Number 3	Township Number 28	Range Number EW
County: Wichita					
Distance and direction from nearest town or city street address of well if located within city?					
2 WATER WELL OWNER: Jim D. Gooch c/o Homer Morgan					
RR#, St. Address, Box #: 2110 Industrial, Wichita, KS 67216					
City, State, ZIP Code: Wichita, KS 67216					
Board of Agriculture, Division of Water Resources					
Application Number: mw-5					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 20 ft. ELEVATION: 15.06			
		Depth(s) Groundwater Encountered 1.14.9 ft. 2. 15.06 ft. 3. 09-10-96 ft.			
		WELL'S STATIC WATER LEVEL 15.06 ft. below land surface measured on mo/day/yr 09-10-96			
		Pump test data: Well water was 8.625 ft. after 20 hours pumping gpm			
		Est. Yield gpm Well water was 8.625 ft. after 20 hours pumping gpm			
Bore Hole Diameter 8.625 in. to 20 ft. and in. to ft.		WELL WATER TO BE USED AS:			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		5 Public water supply 8 Air conditioning 11 Injection well			
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well		WAS A chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted mw-5			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped X			
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded X		2 PVC 4 ABS 7 Fiberglass 8 Concrete tile 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)			
Blank casing diameter 2 in. to 10 ft. Dia SCH 40 PVC lbs./ft. Wall thickness or gauge No. 10		Type of Screen or Perforation Material:			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From 10 ft. to 20 ft. From 10 ft. to 20 ft.			
GRAVEL PACK INTERVALS:		From 9 ft. to 20 ft. From 9 ft. to 20 ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other			
Grout Intervals: From 2 ft. to 0 ft. From 7 ft. to 7 ft. From 9 ft. to 9 ft.		What is the nearest source of possible contamination:			
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)		13 Insecticide storage Contaminated Si			
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
GL	1.00	asphalt, fill			
1.00	7.00	Silty Clay (CL)			
7.00	14.00	Sandy Silt (ML)			
14.00	20.00	Sand (SP)			
20.00	TD	End of borehole			
Flush Mount					
waiver					
D. Taylor					
06-24-96					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 09-10-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 585 This Water Well Record was completed on (mo/day/yr) 09-19-96 under the business name of Associated Environmental, Inc. by (signature) D. Taylor					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send for three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4