

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u> Fraction: <u>NE 1/4 NW 1/4 NW 1/4</u> Section Number: <u>17</u> Township Number: <u>T 28 S</u> Range Number: <u>R 1 E</u>	
Distance and direction from nearest town or city street address of well if located within city? <u>901 W. MacArthur Rd., Wichita, KS</u>	
2 WATER WELL OWNER: <u>OXY USA, Inc.</u> RR#, St. Address, Box #: <u>110 W. 7th St.</u> Board of Agriculture, Division of Water Resources City, State, ZIP Code: <u>Tulsa, OK 74119</u> Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: <u>20</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. <u>12</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: <u>8.75</u> in. to <u>20</u> ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 1 Domestic 2 Irrigation 8 Air conditioning 6 Oil field water supply 4 Industrial 7 Lawn and garden only 11 Injection well 9 Dewatering 10 Monitoring well 12 Other (Specify below) <u>Air sparge #6</u> Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No
5 TYPE OF BLANK CASING USED: 1 Steel <u>2 PVC</u> Blank casing diameter <u>2</u> in. to <u>18</u> ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface: <u>Flush mount</u> in., weight lbs./ft. Wall thickness or gauge No. <u>Sch. 40</u> 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) Casing joints: Glued Clamped Welded Threaded <u>Flush ft.</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass SCREEN OR PERFORATION OPENINGS ARE: <u>1</u> Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Fiberglass 6 Concrete tile 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 RMP (SR) 9 ABS 8 Saw cut 9 Drilled holes 10 Other (specify) 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) SCREEN-PERFORATED INTERVALS: From <u>18</u> ft. to <u>20</u> ft., From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>16</u> ft. to <u>20</u> ft., From ft. to ft., From ft. to ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: 3 From <u>14'</u> ft. to <u>16'</u> ft., 1 From <u>3'</u> ft. to <u>14'</u> ft., 2 From <u>0</u> ft. to <u>3'</u> ft. What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) <u>Former fuel storage & processing on site</u> Direction from well? How many feet?	
FROM TO LITHOLOGIC LOG	FROM TO PLUGGING INTERVALS
0 2' Sand fine grain	
2' 8' Silty sand, fine grain	
8' 15' Clayey silty sand, med-fine grain	
15' 20' sand with some clayey silt, coarse grain	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>12/16 - 12/20/96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>603</u> This Water Well Record was completed on (mo/day/yr) <u>1/8/97</u> under the business name of <u>Whitetail Services, Inc</u> by (signature) <u>[Signature]</u>	