

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		<u>NE 1/4 NW 1/4 NW 1/4</u>	<u>17</u>	T <u>28</u> S	R <u>1</u> <u>EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>901 W. MacArthur Rd., Wichita, KS</u>					
2 WATER WELL OWNER: <u>OXY USA, Inc.</u>					
RR#, St. Address, Box #: <u>110 W. 7th St.</u>				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code: <u>Tulsa, Ok 74119</u>				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>20</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>12</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: <u>8.75</u> in. to <u>20</u> ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>Air Sparge #13</u>			
		Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
2 <u>PVC</u>		4 ABS		6 Asbestos-Cement	
				7 Fiberglass	
Blank casing diameter <u>2</u> in. to <u>18</u> ft., Dia				8 Concrete tile	
Casing height above land surface <u>Flush mount</u> in., weight				9 Other (specify below)	
				Casing JOINTS: Glued Clamped	
				Welded	
				Threaded <u>Flush Jt.</u>	
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel		5 Fiberglass	
2 Brass		4 Galvanized steel		6 Concrete tile	
				7 <u>PVC</u>	
				8 RMP (SR)	
				9 ABS	
				10 Asbestos-cement	
				11 Other (specify)	
				12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot		5 Gauzed wrapped	
2 Louvered shutter		4 Key punched		6 Wire wrapped	
				7 Torch cut	
				8 Saw cut	
				9 Drilled holes	
				10 Other (specify)	
				11 None (open hole)	
SCREEN-PERFORATED INTERVALS: From <u>18</u> ft. to <u>20</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>16</u> ft. to <u>20</u> ft., From ft. to ft.					
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: <u>3</u> From <u>14</u> ft. to <u>16</u> ft. / From <u>3</u> ft. to <u>14</u> ft. / From <u>0</u> ft. to <u>3</u> ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines		7 Pit privy	
2 Sewer lines		5 Cess pool		8 Sewage lagoon	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	
				10 Livestock pens	
				11 Fuel storage	
				12 Fertilizer storage	
				13 Insecticide storage	
				14 Abandoned water well	
				15 Oil well/Gas well	
				16 Other (specify below)	
				<u>Former fuel Storage & processing on site</u>	
Direction from well?					
How many feet?					
PLUGGING INTERVALS					
FROM	TO	LITHOLOGIC LOG		FROM	TO
<u>0</u>	<u>2'</u>	<u>sand fine grain</u>			
<u>2'</u>	<u>8'</u>	<u>silty sand fine grain</u>			
<u>8'</u>	<u>15'</u>	<u>clayey silty sand, med-fine grain</u>			
<u>15'</u>	<u>20'</u>	<u>sand with some clayey silt, coarse grain</u>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>12/16 - 12/20/96</u> and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. <u>603</u> This Water Well Record was completed on (mo/day/yr) <u>1/18/97</u>					
under the business name of <u>Whitetail Services, Inc.</u> by (signature) <u>[Signature]</u>					