

1) LOCATION OF WATER WELL:		Fraction	Form WWC-3		RSA 62a-1212	Township Number		Range Number	
County: Sedgwick		NE 1/4 NW 1/4 NW 1/4		17		T 28 S		R 1 E/W	
Distance and direction from nearest town or city street address of well if located within city? 901 W. MacArthur Rd., Wichita, KS									
2) WATER WELL OWNER: OXY USA, Inc. RR#, St. Address, Box #: 110 W. 7th St. City, State, ZIP Code: Tulsa, OK 74119 Board of Agriculture, Division of Water Resources Application Number:									
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4) DEPTH OF COMPLETED WELL: 20 ft. ELEVATION:						
			Depth(s) Groundwater Encountered 1. 12 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8.75 in. to 20 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes. No. X Aik Spurge #14 Water Well Disinfected? Yes No						
5) TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 18 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface Flush mount in. weight lbs./ft. Wall thickness or gauge No. Sch. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 18 ft. to 20 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 16 ft. to 20 ft. From ft. to ft.									
6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: 3 From 14 ft. to 16 ft. 1 From 3 ft. to 14 ft. 2 From 0 ft. to 3 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? How many feet? Former fuel storage & processing on site. PLUGGING INTERVALS									
LITHOLOGIC LOG FROM TO 0 2' Sand fine grain 2' 8' Silty sand fine grain 8' 15' Clayey silty sand med-fine grain 15' 20' Sand with some clayey silty coarse grain									
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/16 - 12/20/96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 603 This Water Well Record was completed on (mo/day/yr) 11/8/97 under the business name of White Tail Services Inc. by (signature) [Signature]									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									