

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u> Fraction: <u>NE 1/4 NW 1/4 NW 1/4</u> Section Number: <u>17</u> Township Number: <u>T 28 S</u> Range Number: <u>R 1 E</u>			
Distance and direction from nearest town or city street address of well if located within city? <u>901 W. MacArthur Rd., Wichita KS</u>			
2 WATER WELL OWNER: <u>OXY USA, Inc.</u> RR#, St. Address, Box #: <u>110 W. 7th St.</u> Board of Agriculture, Division of Water Resources City, State, ZIP Code: <u>Tulsa, OK 74119</u> Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: <u>20</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. <u>12</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: <u>8.75</u> in. to <u>20</u> ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>Air Sparge #18</u> Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No		
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped <u>2 PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>2</u> in. to <u>18</u> ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface: <u>Flush mount</u> in., weight lbs./ft. Wall thickness or gauge No. <u>Sch. 40</u> TYPE OF SCREEN OR PERFORATION MATERIAL: <u>7 PVC</u> 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: <u>1</u> Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From ft. to <u>20</u> ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>16</u> ft. to <u>20</u> ft., From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: <u>3</u> From <u>14</u> ft. to <u>16</u> ft. 1 From <u>3</u> ft. to <u>14</u> ft. 2 From <u>0</u> ft. to <u>3</u> ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? <u>Former fuel storage & processing on site</u> How many feet?			
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS			
0' 2'	sand fine grain		
2' 8'	silty sand fine grain		
8' 15'	clayey silty sand, med-fine grain		
15' 20'	sand with some clayey silt, coarse grain		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>12/16 - 12/20/96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>603</u> This Water Well Record was completed on (mo/day/yr) <u>12/19/97</u> under the business name of <u>Whitetail Services, Inc.</u> by (signature) <u>[Signature]</u>			