

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: <u>Sedgewick</u>		<u>NE 1/4 NW 1/4 NW 1/4</u>		<u>17</u>		<u>T 28 S</u>		<u>R 1 E</u>	
Distance and direction from nearest town or city street address of well if located within city? <u>901 W. Mac Arthur Rd., Wichita Wichita, KS</u>									
2 WATER WELL OWNER: <u>OXYGEN USA, INC.</u>									
RR#, St. Address, Box # : <u>110 W. 7th St.</u>									
City, State, ZIP Code : <u>Tulsa, OK 74119</u>									
Board of Agriculture, Division of Water Resources Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>20</u> ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. <u>12</u> ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter <u>8.75</u> in. to <u>20</u> ft., and in. to ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>Air Sparge #21</u>							
		Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes No							
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped									
2 <u>PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded									
Blank casing diameter <u>2</u> in. to <u>18</u> ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface <u>Flushmount</u> in., weight lbs./ft. Wall thickness or gauge No. <u>Sch. 40</u>									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
SCREEN-PERFORATED INTERVALS: From <u>18</u> ft. to <u>20</u> ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From <u>16</u> ft. to <u>20</u> ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: 3 From <u>14</u> ft. to <u>16</u> ft., 1 From <u>3</u> ft. to <u>14</u> ft., 2 From <u>0</u> ft. to <u>3</u> ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
Direction from well? <u>Former Fuel Storage</u>									
How many feet? <u>processing onsite</u>									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>12/16 - 12/20/96</u> and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. <u>603</u> This Water Well Record was completed on (mo/day/yr) <u>12/18/97</u>									
under the business name of <u>Whitetail Service, Inc.</u> by (signature) <u>[Signature]</u>									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4