

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		<u>NE 1/4 NW 1/4 NW 1/4</u>	<u>17</u>	<u>T 28 S</u>	<u>R 1 E/W</u>
Distance and direction from nearest town or city street address of well, if located, within city? <u>901 W. MacArthur Rd., Wichita, KS</u>					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # : <u>Oxy ust, Inc</u> <u>110 W. 7th St.</u>		Application Number:			
City, State, ZIP Code : <u>Tulsa, OK 74119</u>					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>20</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>12</u> ft. 2. <u>12</u> ft. 3. <u>12</u> ft.			
		WELL'S STATIC WATER LEVEL <u>12</u> ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was <u>12</u> ft. after <u>12</u> hours pumping <u>12</u> gpm			
		Est. Yield <u>12</u> gpm: Well water was <u>12</u> ft. after <u>12</u> hours pumping <u>12</u> gpm			
		Bore Hole Diameter <u>8.75</u> in. to <u>20</u> ft., and <u>20</u> in. to <u>20</u> ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>Air Spage # 23</u>			
		Was a chemical/bacteriological sample submitted to Department? Yes <u>No X</u> If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <u>No</u>			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued <u>Clamped</u>			
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded					
2 PVC 4 ABS 7 Fiberglass Threaded <u>Flush ft</u>					
Blank casing diameter <u>2</u> in. to <u>18</u> ft. Dia <u>18</u> in. to <u>18</u> ft. Dia <u>18</u> in. to <u>18</u> ft.					
Casing height above land surface <u>Flush mount</u> in. weight <u>18</u> lbs./ft. Wall thickness or gauge No. <u>Sch. 40</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>18</u> ft. to <u>20</u> ft. From <u>18</u> ft. to <u>20</u> ft.					
GRAVEL PACK INTERVALS: From <u>16</u> ft. to <u>20</u> ft. From <u>16</u> ft. to <u>20</u> ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		Grout Intervals: 3 From <u>14</u> ft. to <u>16</u> ft. From <u>3</u> ft. to <u>14</u> ft. 2 From <u>0</u> ft. to <u>3</u> ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)		<u>Former Fuel Storage</u>			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage		<u>Processing On Site</u>			
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2'	Sand, th grain			
2'	8'	Silty sand, th grain			
8'	15'	Clayey silty sand, md.-th grain			
15'	20'	Sand with some clayey silt, ch grain			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>12-16 thru 12-20-96</u> and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. <u>603</u> This Water Well Record was completed on (mo/day/yr) <u>5-8-97</u>					
under the business name of <u>Whitetail Services, Inc.</u> by (signature) <u>John C. Schum</u>					