

1 LOCATION OF WATER WELL: Sedgwick	FRACTION SW 1/4 SW 1/4 SE 1/4	Section Number 17	Township Number T 28 S	Range Number R 1E E/W
Distance and direction from nearest town or city street address of well if located within city? NW Corner of 47th S. and Palisade Wichita, Kansas				
WATER WELL OWNER: EBY CONSTRUCTION		Board of Agriculture, Division of Water Resource		
RR#, ST. ADDRESS, BOX #: 610 N. Main		Application Number: 990224		
CITY, STATE, ZIP CODE: Wichita, Kansas		67203		

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 45 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 12 FT. BELOW LAND SURFACE MEASURED ON 11/16/1999 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 45 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No
--	---

5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing Diameter 8 in. to 20 ft., Dia in. to ft. Casing height above land surface 12 in., weight 5.52 lbs. / ft. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATION INTERVALS: from 20 ft. to 45 ft., From ft. to ft. GRAVEL PACK INTERVALS: from 20 ft. to 45 ft., From ft. to ft.	8 Concrete tile CASING JOINTS: Glued X Clamped 9 Other (Specify below) Welded SDR - 26 Threaded Wall thickness or gauge No. .332 10 Asbestos-cement 11 other (specify) 12 None used (open hole)	13 Insecticide storage 14 Abandon water well 15 Oil well/Gas well 16 Other (specify below) None Apparent
---	---	---

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 13 Insecticide storage 14 Abandon water well 15 Oil well/Gas well 16 Other (specify below) None Apparent	Direction from well? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 2 topsoil 2 20 fine sand 20 38 medium coarse sand 38 45 medium sand	How many feet? FROM TO PLUGGING INTERVALS 0 2 2 20 20 38 38 45
--	---	---

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/16/1999 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 11/18/99 Under the business name of Harp Well & Pump by (signature)	<i>Todd S. Harp</i>
---	---------------------