

1 LOCATION OF WATER WELL:		Fraction SE <u>SE</u> SE <u>SE</u> SE <u>SE</u>		Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		1/4 <u>1/4</u> 1/4 <u>1/4</u>		<u>20</u>	T <u>28</u> S	R <u>1</u> <u>EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>5611 S. Broadway Wichita</u>						
2 WATER WELL OWNER: <u>BDAT Environmental (Outkrip Corporation)</u>						
RR#, St. Address, Box #: <u>1862 Craigshire (901 N. Mingo Rd.)</u>				Board of Agriculture, Division of Water Resources		
City, State, ZIP Code: <u>St. Louis, MO 63146 (Tulsa, OK 74101)</u>				Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>20</u> ft. ELEVATION:				
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.				
		WELL'S STATIC WATER LEVEL <u>12.37</u> ft. below land surface measured on mo/day/yr <u>8/13/99</u>				
		Pump test data: Well water was ft. after hours pumping gpm				
		Est. Yield gpm: Well water was ft. after hours pumping gpm				
		Bore Hole Diameter <u>8</u> in. to ft., and in. to ft.				
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well				
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)				
		2 Irrigation 4 Industrial 7 Lawn and garden only <u>10</u> Monitoring well				
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted				
		Water Well Disinfected? Yes No				
5 TYPE OF BLANK CASING USED:						
1 Steel		3 RMP (SR)		5 Wrought iron		8 Concrete tile
<u>2</u> PVC		4 ABS		6 Asbestos-Cement		9 Other (specify below)
				7 Fiberglass		CASING JOINTS: Glued Clamped
Blank casing diameter <u>2</u> in. to <u>10</u> ft., Dia						Welded
Casing height above land surface <u>0</u> in., weight						Threaded <u>X</u>
TYPE OF SCREEN OR PERFORATION MATERIAL:				<u>7</u> PVC		10 Asbestos-cement
1 Steel		3 Stainless steel		8 RMP (SR)		11 Other (specify)
2 Brass		4 Galvanized steel		9 ABS		12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:				5 Gauzed wrapped		8 Saw cut
1 Continuous slot		<u>3</u> Mill slot		6 Wire wrapped		11 None (open hole)
2 Louvered shutter		4 Key punched		7 Torch cut		9 Drilled holes
SCREEN-PERFORATED INTERVALS: From <u>10</u> ft. to <u>20</u> ft., From ft. to ft., From ft. to ft.						10 Other (specify)
GRAVEL PACK INTERVALS: From <u>7</u> ft. to <u>20</u> ft., From ft. to ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>3</u> Bentonite 4 Other						
Grout Intervals: From <u>1</u> ft. to <u>7</u> ft., From ft. to ft., From ft. to ft.						
What is the nearest source of possible contamination:						
1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens
2 Sewer lines		5 Cess pool		8 Sewage lagoon		14 Abandoned water well
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		<u>1</u> Fuel storage
						12 Fertilizer storage
						15 Oil well/Gas well
						16 Other (specify below)
						13 Insecticide storage
Direction from well? <u>ESE</u>						How many feet? <u>200</u>
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS						
<u>0</u> <u>8.5</u> <u>Brown silty clay with sand</u> <u>0</u> <u>20</u> <u>chip bentonite</u>						
<u>8.5</u> <u>20</u> <u>Tan Sand</u>						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or <u>3</u> plugged under my jurisdiction and was completed on (mo/day/year) <u>5/19/00</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>634</u> This Water Well Record was completed on (mo/day/yr) <u>8/22/00</u> under the business name of <u>Shirley Enviro</u> by (signature) <u>Charles Engle</u>						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						