

MW#8

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>SEDGWICK</u>		<u>SW 1/4 SW 1/4 SE 1/4</u>	<u>8</u>	T <u>28-S</u>	R <u>1</u> <u>EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>3838 S. Gold St. Wichita KS</u>					
2 WATER WELL OWNER: <u>Consolidated Freightways</u> RR#, St. Address, Box # : <u>3838 S. Gold St.</u> City, State, ZIP Code : <u>Wichita KS 67217</u>				Board of Agriculture, Division of Water Resources Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>17</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>17</u> ft. 2. <u>17</u> ft. 3. <u>17</u> ft. WELL'S STATIC WATER LEVEL <u>17</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was <u>17</u> ft. after <u>17</u> hours pumping <u>17</u> gpm Est. Yield <u>17</u> gpm: Well water was <u>17</u> ft. after <u>17</u> hours pumping <u>17</u> gpm Bore Hole Diameter: <u>7 1/4</u> in. to <u>17</u> ft., and <u>17</u> in. to <u>17</u> ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) <u>10</u> Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes. <u>No</u> ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <u>No</u>			
		Casing JOINTS: Glued. <u>No</u> Clamped. <u>No</u>			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded <u>No</u>
<u>PVC</u>		4 ABS	7 Fiberglass		Threaded <u>X</u>
Blank casing diameter <u>2</u> in. to <u>7</u> ft., Dia. <u>2</u> in. to <u>7</u> ft., Dia. <u>2</u> in. to <u>7</u> ft.					
Casing height above land surface <u>0</u> in., weight <u>Sched 40</u> lbs./ft. Wall thickness or gauge No. <u>40</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		<u>2</u> Mill slot <u>0.10</u>	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
7 Torch cut 10 Other (specify) <u>200'</u>					
SCREEN-PERFORATED INTERVALS: From <u>17</u> ft. to <u>7</u> ft., From <u>17</u> ft. to <u>7</u> ft., From <u>17</u> ft. to <u>7</u> ft.					
GRAVEL PACK INTERVALS: From <u>17</u> ft. to <u>5</u> ft., From <u>17</u> ft. to <u>5</u> ft., From <u>17</u> ft. to <u>5</u> ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other <u>200'</u>					
Grout Intervals: From <u>2</u> ft. to <u>3</u> ft., From <u>5</u> ft. to <u>2</u> ft., From <u>5</u> ft. to <u>2</u> ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	<u>11</u> Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? <u>NN</u>		How many feet? <u>200'</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>8"</u>	<u>Asphalt</u>			
<u>8"</u>	<u>1.5</u>	<u>Base Rock 3 1/4"</u>			
<u>1.5</u>	<u>7</u>	<u>Brn Silty Clay</u>			
<u>7</u>	<u>12</u>	<u>Med Sand</u>			
<u>12</u>	<u>17</u>	<u>Wet Med to Coarse Sand</u>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>1</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3-2-01</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. <u>575</u> This Water Well Record was completed on (mo/day/yr) <u>3-29-01</u> under the business name of <u>FUNKIE DRILLING SERVICE INC</u> by (signature) <u>[Signature]</u>					