

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgewick</u>		<u>NE</u> $\frac{1}{4}$ <u>NW</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$	<u>4</u>	T <u>28</u> S	R <u>1</u> <u>EW</u>

Distance and direction from nearest town or city street address of well if located within city?
1/2 block W of Intersection of Scott and Pattie (N. side) in Wichita, Ks 560A

2 WATER WELL OWNER: City of Wichita

RR#, St. Address, Box # : 1900 E. 9th

City, State, ZIP Code : Wichita Ks 67214

Board of Agriculture, Division of Water Resources

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile

W E

N S

Section Box Diagram: A 2x2 grid with dashed lines. The quadrants are labeled NW, NE, SW, and SE. An 'X' is marked in the NE quadrant.

4 DEPTH OF COMPLETED WELL... 30.55 ... ft. ELEVATION:

Depth(s) Groundwater Encountered 1. 14 ... ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter: 3.25 ... in. to 30.0 ... ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		9 Dewatering
		10 Monitoring well
		12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☒ If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes ☐ No ☒

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
② PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
		7 Fiberglass		Threaded. ☒

Blank casing diameter . . . 1 . . . in. to 25.42 . . . ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 0 . . . in., weight lbs./ft. Wall thickness or gauge No. 56.80

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	⑦ PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	③ Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS:

From . . . 25.42 . . . ft. to . . . 30.55 . . . ft., From ft. to ft.
From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS:

From . . . 22.7 . . . ft. to . . . 30.8 . . . ft., From ft. to ft.
From ft. to ft., From ft. to ft.

6] GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:		From 0 ft. to 22.7 ft.	From	ft. to	ft. to
What is the nearest source of possible contamination:			10 Livestock pens		
1 Septic tank	4 Lateral lines	7 Pit privy	14 Abandoned water well		
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage		
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage		
			13 Insecticide storage		
Direction from well?			16 Other (specify below)		
			How many feet?		

[illegible]

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-27-02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 604 This Water Well Record was completed on (mo/day/yr) 3-3-02 under the business name of Environmental Priority Service, Inc by (signature) [Signature]