

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		1/4 NW 1/4 SE 1/4	29	T 28 S	R 1 W
Distance and direction from nearest town or city street address of well if located within city?					
From 63rd Street South and Broadway 1/4 mile North and 1/4 mile West					
2 WATER WELL OWNER: Gerald Blood					
RR#, St. Address, Box #: 6346 S. Broadway St					
City, State, ZIP Code: Wichita, KS 67216					
Board of Agriculture, Division of Water Resources					
Application Number: 45,635					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 55' ft. ELEVATION:			
		Depth(s) Groundwater Encountered 14' ft. 2' ft. 3' ft.			
		WELL'S STATIC WATER LEVEL 14' ft. below land surface measured on mo/day/yr 12-19-03			
		Pump test data: Well water was 25' ft. after 12 hours pumping 900 gpm			
		Est. Yield 800 gpm: Well water was 25' ft. after 12 hours pumping 900 gpm			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
7 Fiberglass Threaded					
Blank casing diameter 16 in. to 35 ft., Dia 16 in. to 16 ft., Dia 16 in. to 16 ft.					
Casing height above land surface 12 in., weight 16 lbs./ft. Wall thickness or gauge No. 1/2"					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement					
2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify)					
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 2 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 35 ft. to 55 ft., From 35 ft. to 55 ft., From 35 ft. to 55 ft.					
GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 20 ft. to 55 ft., From 20 ft. to 55 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 3 ft. to 20 ft., From 3 ft. to 20 ft., From 3 ft. to 20 ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? None Open Field					
How many feet? Open Field					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0 2 Sandy Topsoil					
2 5 Clay					
5 18 Medium Sand					
18 20 Clay					
20 54 Medium to Large Gravel					
54 55 Blue Clay					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-19-03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 238 This Water Well Record was completed on (mo/day/yr) 12-22-03 under the business name of Weninger Irrigation by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.					