

LOCATION OF WATER WELL:		FRACTION	SECTION NUMBER	TOWNSHIP NUMBER	RANGE NUMBER
Sedgwick		SE 1/4 NW 1/4 NE 1/4	16	T 28 S	R 1E E/W
Distance and direction from nearest town or city street address of well if located within city?					
1223 E. Selma Wichita, Kansas					
WATER WELL OWNER: ROSS, Tom					
RR#,ST. ADDRESS,BOX #: 1415 Hannah					
CITY, STATE: Haysville, Kansas					
ZIP CODE: Application Number:					
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		DEPTH OF PLUGGED WELL: 27 ft. ELEVATION:			
		Depth of groundwater Encountered: ft.			
		WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 5/9/05			
		Pump test data: Well water was ft. after hours of pumping @ gpm			
		Well water was ft. after hours of pumping @ gpm			
		Bore Hole Diameter in. to ft. and in. to ft.			
		WELL WATER WAS USED AS:			
		1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well			
		2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)			
		Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted			
		Was Water Well Disinfected? YES NO			
TYPE OF CASING USED:					
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded					
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile Welded Clamped					
Blank casing diameter 1 1/4 in. to ft., Dia. in. to ft., Dia. in. to ft.					
Casing height below land surface: 60 in., Weight: lbs. / ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) N/A					
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)					
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) N/A					
SCREEN - PERFORATION INTERVAL From ft. to ft., From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft.					
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug					
Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft., From 2 ft. to 27 ft.					
What is the nearest source of possible contamination:					
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well					
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)					
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage None Apparent					
Direction from well? How many feet?					
From To LITHOLOGIC LOG From To LITHOLOGIC LOG					
0 2 surface clay and silt					
2 27 bentonite hole plug					
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and					
was completed on (mo/day/year) 5-9-2005 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 5-11-2005					
under the business name of Harp Well & Pump Service Inc. by (signature) Todd S. Harp					