

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>	<u>SE 1/4 SE 1/4 NW 1/4</u>	<u>36</u>	T <u>28S</u> S	R <u>1E</u> E/W

Distance and direction from nearest town or city street address of well if located within city?
2236 Duck Creek Ln.

2 WATER WELL OWNER:	RR#, St. Address, Box #	City, State, ZIP Code	Board of Agriculture, Division of Water Resources Application Number:
<u>Roger Campbell</u>	<u>2236 Duck Creek Ln.</u>	<u>Derby, KS</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	ft. ELEVATION:
	<u>100</u>	<u>5125/05</u>

Depth(s) Groundwater Encountered 1 50 ft. 2 50 ft. 3 5125/05 ft.
WELL'S STATIC WATER LEVEL 50 ft. below land surface measured on mo/day/yr
Pump test data: Well water was 50 ft. after 5125/05 hours pumping gpm
Est. Yield gpm: Well water was 50 ft. after 5125/05 hours pumping gpm
WELL WATER TO BE USED AS:
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 5 Public water supply 8 Air conditioning 10 Monitoring well
Domestic (lawn & garden)

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	7 Fiberglass		Threaded
3 RMP (SR)			
4 ABS			

Blank casing diameter 5 in. to 100 ft., Dia 16 in. to 160 lbs./ft. Wall thickness or gauge No. 26
Casing height above land surface 16 in., weight 160 lbs./ft. Wall thickness or gauge No. 26

TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement
2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify)
12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)
7 Torch cut

SCREEN-PERFORATED INTERVALS: From 80 ft. to 100 ft., From 24 ft. to 100 ft.
GRAVEL PACK INTERVALS: From 24 ft. to 100 ft., From 24 ft. to 100 ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From <u>4</u> ft. to <u>24</u> ft., From <u>24</u> ft. to <u>100</u> ft., From <u>100</u> ft. to <u>100</u> ft.				

What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage

Direction from well? East How many feet? 45

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	topsoil			
2	61	clay			
61	71	fine sand-clay			
71	79	fine sand			
79	97	shale			
97	100	limestone			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5/25/05</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. <u>618105</u> This Water Well Record was completed on (mo/day/yr) <u>6/18/05</u> under the business name of <u>Chase Drilling</u> by (signature) <u>R Chase</u>
--