

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Sedgwick	FRACTION SE 1/4 NE 1/4 SE 1/4	SECTION NUMBER 22	TOWNSHIP NUMBER T 28 S	RANGE NUMBER R 1E E/W
Distance and direction from nearest town or city street address of well if located within city? 150' West of Idlewild				
2 WATER WELL OWNER: OAKLAWN IMPROVEMENT DISTRICT RR#,ST. ADDRESS,BOX #: 2937 Oaklawn Dr. CITY, STATE: Wichita, Kansas ZIP CODE: 67216				
Board of Agriculture, Division of Water Resource Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 35 ft. ELEVATION: Depth of groundwater Encountered: ft. WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON 3/28/07 Pump test data: Well water was ft. after hours of pumping @ gpm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm Bore Hole Diameter 14 in. to 35 ft. and in. to ft. WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning Was a chemical/bacteriological sample submitted to Department? YES NO Was Water Well Disinfected? YES NO			
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26 Welded Clamped Blank casing diameter 5 in. to 20 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL From 20 ft. to 30 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 24 ft. to 35 ft., From ft. to ft. From ft. to ft., From ft. to ft.				

6	GROUT MATERIALS:		1. Neat cement	2. Cement Grout	3. Bentonite	Other	bentonite hole plug		
	Grout Intervals:	From	0 ft.	to	20 ft.	From	ft.	to	ft.
What is the nearest source of possible contamination:									
1. Septic tank		4. Lateral lines		7. Pit privy		10. Livestock pens		13. Insecticide storage	
2. Sewer lines		5. Cess Pool		8. Sewage lagoon		11. Fuel storage		14. Abandon water well	
3. Watertight sewer line		6. Seepage pit		9. Feed yard		12. Fertilizer storage		15. Oil well/Gas well	
Direction from well?		East				How many feet?		50 ft. plus	
16. Other (specify below)									

[illegible]

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. **reconstructed** or 3. **plugged** under my jurisdiction and was completed on (mo/day/year) **3-28-2007** and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) **3-28-2007**

under the business name of **Harp Well and Pump Service** by (signature) *Todd S. Harp*