


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Sedgwick	SW 1/4 SW 1/4 NE 1/4	11	T 28 S	R 1 E/W

Distance and direction from nearest town or city street address of well if located within city?

Approximately 1/8 mile south and 1/8 mile east of Wichita

2 WATER WELL OWNER:	Boeing Company	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	3801 S. Oliver	Application Number: N/A
City, State, ZIP Code :	Wichita, KS 67210	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 43 ft. ELEVATION: unknown
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL . . . 31.3 . . . ft. below land surface measured on mo/day/yr 11-10-92 Pump test data: Well water was not ch'd . . . ft. after hours pumping gpm Est. Yield unknown gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter . . . 11 . . . in. to . . . 43 . . . ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Recovery Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued . X . . . Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 18 ft., Dia in. to ft., Dia in. to ft.			Threaded
Casing height above land surface 24 in., weight 2.87 lbs./ft. Wall thickness or gauge No. 265			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
11 Other (specify)			12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 18 ft. to 41 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 16 ft. to 43 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other . . Bentonite Holeplug
Grout Intervals: From ft. to ft., From ft. to ft., From 0 ft. to 16 ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	14 Abandoned water well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	15 Oil well/Gas well
			13 Insecticide storage	16 Other (specify below)
Direction from well?			How many feet?	Ground already contaminated

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Fill	38.5	40	Clay, light gray
5	6.5	Clay, gray	40	43	Shale, dark gray
6.5	9	Clay, tan, brown			
9	11	Clay, sandy, tan, soft			
11	15	Clay, tan, brown			
15	22	Clay, little sandy, tan, brown			
22	23	Clay, tan, brown, with red and olive gray			
23	31	Clay, light olive tan			
31	32.5	Clay, sandy, tan			
32.5	33	Clay, brown			
33	34.5	Sand			
34.5	35	Clay, olive gray			
35	36	Sandstone			
36	38.5	Clay, yellow, brown, olive gray			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-6-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 2-25-93 under the business name of Clarke Well & Equipment, Inc. by (signature) <i>Clarke Well & Equipment, Inc.</i>
